



ssclib

February 23, 2011

Abstract

Library of Fortran 90 (and Perl) utilities needed for SAS task development.

1 Description

1.1 Introduction

This library consists of a series of Fortran 90 modules useful for the development of SAS tasks. Each module is described in a separate section below. Each module is contained in a separate file and will be compiled separately. The resulting object files will be combined into a single library file.

The modules divide broadly into (i) those which depend on XMM-specific libraries such as **dal**, **cal** and **errorHandling**, and (ii) those which do not. The only foreign module that members of the second group depend on is called **types** and is at present resident in the sas package **utils**. This small module just defines data types such as int8, bool etc. If it is desired to port the non XMM-specific modules to a non-sas environment it is recommended to also copy this **types** module.

At some stage in the future it may be desirable to move these two groups into separate libraries.

1.2 Angle conventions

All angular variables are assumed to be in radians, unless otherwise indicated. Variable names end in the unit (eg arcsec, deg) if it is not radians.

1.3 Dependency relations:

*** Not yet done this figure.

1.4 Module index

- Section 2: `array_utils`:
- Section 3: `cal_aux`:



- Section 4: `confusion`:
- Section 5: `constants`:
- Section 6: `coordinate`:
- Section 7: `dal_aux`:
- Section 8: `detection_stats`:
- Section 9: `dss_aux`:
- Section 10: `dump`:
- Section 11: `ellipse`:
- Section 12: `exposure`:
- Section 13: `fftw_aux`:
- Section 14: `geometric_types`:
- Section 15: `histogram_utils`:
- Section 16: `intervals_aux`:
- Section 17: `linear`:
- Section 18: `math_utils`:
- Section 19: `minimizations`:
- Section 20: `oal_aux`:
- Section 21: `parse_list_mod`:
- Section 22: `polygon`:
- Section 23: `psf_ims`:
- Section 24: `random_aux`:
- Section 25: `reallocate`:
- Section 26: `rebinnings`:
- Section 27: `save_image`:
- Section 28: `sort_mod`:
- Section 29: `source_cutouts`:
- Section 30: `splines`:
- Section 31: `ssc_misc`:
- Section 32: `test_utils`:
- Section 33: `warp_utils`:
- Section 34: `wcs_aux`:
- Section 35: `SSCLib` (Perl):
- Section 36: `Coords` (Perl):
- Section 37: `CelCoords` (Perl):



2 General-purpose array-processing utilities

Module name: `array_utils`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)
Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

2.1 aryStatInfoFlagT structure definition

A set of structure definitions is provided. This consists of one of the elements in type(aryStatInfo???T) (see Sec 2.2), and also is used as an argument in some subroutines/functions in this package. See Sec 2.2 and Table 1 for the (supposed) meaning of each element.

```
type, public :: aryStatInfoFlagT
    integer      :: status = 0 ! Normal
    logical      :: isValLowerUsed = .false., isValUpperUsed = .false. &
                   , isAreaLowerUsed = .false., isAreaUpperUsed = .false. &
                   , isMaskUsed = .false.
end type aryStatInfoFlagT
```

2.2 aryStatInfo???T structure definition


A set of structure definitions is provided. The above ‘????’ can be Double, Single, Int32, Int16 or Int8. This gives a structure for the statistics for a given (2-d?) array. The following is the example of `aryStatInfoDoubleT`.

```
type, public :: aryStatInfoDoubleT
    real(double)   :: totalsum, mean, sigma
    real(double)   :: realsum
    integer(int32) :: totalentry, validentry
    real(double)   :: minval, maxval
    integer(int32), dimension(:), allocatable :: minindices, maxindices
    real(double)   :: vallower, valupper
    integer(int32), dimension(:), allocatable :: minareaindices, maxareaindices
    type(aryStatInfoFlagT) :: flag
end type aryStatInfoDoubleT
```

This structure is meant to offer the statistical information of an array or its subset. That is, the statistical information for the array, where the valid entry can be filtered based on given

1. external mask file, where True entry is valid,
2. lower and/or upper thresholds for value at each cell,
3. lower and/or upper boundaries (area, if 2-dim) of the indices of the array cell.

If more than one filter condition are given, then the logical product of those conditions are considered, namely, only the entries that satisfy all the given filter conditions are used. Note that the boundary is

Table 1: Elements in `aryStatInfo`

Element	Type ¹	Description
%totalsum	D/S/I32	Sum (for the valid entry)
%realsum	D	Sum (for the valid entry)
%mean	D (S for SingleT)	Mean
%sigma	D (S for SingleT)	Standard deviation ²
%totalentry	I32	Total entry (size) of the array.
%validentry	I32	The entry used in calculation.
%minval	D/S/I32/I16/I8	Minimum value among the valid entry.
%maxval	D/S/I32/I16/I8	Minimum value among the valid entry.
%minindices	I32 [Array]	Location (indices: x,y,...) of <code>minval</code>
%maxindices	I32 [Array]	Location (indices: x,y,...) of <code>maxval</code>
%vallower	D (S for SingleT)	Lower threshold to be a valid entry (if specified).
%valupper	D (S for SingleT)	Upper threshold to be a valid entry (if specified).
%minareaindices	I32 [Array]	Minimum indices for the area of valid entry.
%maxareaindices	I32 [Array]	Maximum indices for the area of valid entry.
%flag%status	Integer	0 if normal.
%flag%isValLowerUsed	Logical	True if <code>vallower</code> is used.
%flag%isValUpperUsed	Logical	True if <code>valupper</code> is used.
%flag%isAreaLowerUsed	Logical	True if <code>minareaindices</code> is used.
%flag%isAreaUpperUsed	Logical	True if <code>maxareaindices</code> is used.
%flag%isMaskUsed	Logical	True if an external mask is used.

¹: D(Double), S(Single), I32/I16/I8 (Int32/Int16/Int8)

²: $\sqrt{\frac{1}{N} \sum_i (x_i - \bar{x})^2}$.

inclusive for the second and third conditions. For example, if the lower thresholds for value at each cell is given to be 2.5, then the cells of which the value is smaller than 2.5 are regarded as invalid and are not counted as the valid entry.

Table 1 shows the (supposed) meaning of each element as well as gives the difference in types of elements between the structures (such as, `aryStatInfoDoubleT` and `aryStatInfoInt32T`). Technically each user could give a different meaning for them, but it is discouraged for an obvious reason.

Notes: Some of the elements of the structure can be undefined. For example, if `flag%isAreaLowerUsed` is false, the array `minareaindices` is likely to be undefined, even its size (**NOT** allocated). Similarly `flag%isValLowerUsed` is false, `vallower` is likely to be undefined, and so on. If one tries to access those undefined values that may cause a trouble or even Fortran error, leading to abortion.

The difference between the elements of `totalsum` and `realsum` is the type; the latter is always `double`, whereas the former is `double/single/int32`, depending on the type of the input array; n.b., it is `int32` for any of the integer array. The `totalsum` for an integer array may overflow; in that case `totalsum` has a value `INTEGER_NULL`. Another note is that although the they type of `realsum` for a single-precision float array is `double`, obviously it has a practical accuracy of only `single`-precision.

2.3 Array or vector → scalar integers

2.3.1 Return largest true index of a logical vector

```
integer function largestTrueIndex(maskVector)
  logical(bool), intent(in) :: maskVector(:)
end function
```



Examples:

```
largestTrueIndex(((/0, 1, 1/) > 0)) ! returns 3
largestTrueIndex(((/0, 1, 0/) > 0)) ! returns 2
largestTrueIndex(((/0, 0, 0/) > 0)) ! returns 0, ie 1 below vector limit.
```

0 is also returned if the vector is of zero size.

2.3.2 Return smallest true index of a logical vector

```
integer function smallestTrueIndex(maskVector)
    logical(bool), intent(in) :: maskVector(:)
end function
```

Examples:

```
smallestTrueIndex(((/0, 1, 1/) > 0)) ! returns 2
smallestTrueIndex(((/1, 1, 1/) > 0)) ! returns 1
smallestTrueIndex(((/0, 0, 0/) > 0)) ! returns 4, ie 1 above vector limit.
```

size(maskVector)+1 is also returned if the vector is of zero size.

2.3.3 Rectangular bounds of the true area of a logical array

```
subroutine maskArrayLimits(mask, minXi, maxXi, minYi, maxYi)
    logical(bool), intent(in)           :: mask(:, :)
    integer(int16), intent(out)         :: minXi, maxXi, minYi, maxYi
end subroutine
```

!*** erase the status variable from the actual routine!

Example:


```
logical(bool) :: mask(4,5)

mask(1,:) = ((/0, 0, 0, 0, 0/) > 0)
mask(2,:) = ((/0, 1, 1, 0, 0/) > 0)
mask(3,:) = ((/1, 1, 0, 1, 0/) > 0)
mask(4,:) = ((/1, 0, 0, 0, 0/) > 0)

call maskArrayLimits(mask, minXi, maxXi, minYi, maxYi)
! returns minXi=1, maxXi=4, minYi=2, maxYi=4

mask = .false.

call maskArrayLimits(mask, minXi, maxXi, minYi, maxYi)
! returns minXi=6, maxXi=0, minYi=5, maxYi=0 (ie, nonsense)
```



The same nonsense return occurs if mask is of zero size in either direction. It is up to the user to check that the mask is neither empty nor of zero size before calling maskArrayLimits.

2.3.4 Allocate real to a bin

```
function getBinNumber(xBinEdges, x) result(binNum)
    real(single), intent(in) :: xBinEdges(:, x
    integer(int32)          :: binNum
end function
```

In a commonly encountered situation, one has a set of bins defined by a vector of bin edges xBinEdges, plus a real number x, and it is desired to know into which bin x falls. The present function accomplishes this calculation and returns the index of the bin. The bin edges should occur in increasing order, with no two values the same, but they don't have to be equidistant. The returned value obeys in general the rule

$$xBinEdges(i) \leq x < xBinEdges(i + 1) \Rightarrow binNum = i$$

However note the following limiting or pathological cases:

- $x < xBinEdges(1) \Rightarrow binNum = 0$, ie 1 under the lower limit, is returned. It is up to the calling routine to catch these instances if it is necessary to prevent this return value from occurring.
- If $x = xBinEdges(\text{size}(xBinEdges))$ it is judged to fall within the last bin and $binNum = \text{size}(xBinEdges) - 1$ is returned.
- $x > xBinEdges(\text{size}(xBinEdges)) \Rightarrow binNum = \text{size}(xBinEdges)$, ie 1 over the upper limit, is returned. It is up to the calling routine to catch these instances if it is necessary to prevent this return value from occurring.

2.3.5 Simpler maxloc

The fortran routine maxloc(array) returns the indices at which the maximum value in array occurs. However the return must be a vector quantity of the same size as the array has dimensions. This can be slightly clunky if array is of dimension 1 - ie, a 1-dimensional vector. The function maxLoc1d allows one to obtain the index of the maximum value of the 1-D argument in a scalar return value. This can save some lines of code.

```
interface maxLoc1d
    function maxLoc1dSingle(vector, mask)
        real(single), intent(in)           :: vector(:)
        logical(bool), intent(in), optional :: mask(:)
        integer                           :: maxLoc1dSingle
    end function

    function maxLoc1dDouble(vector, mask)
        real(double), intent(in)           :: vector(:)
        logical(bool), intent(in), optional :: mask(:)
    end function
```



```
    integer :: maxLoc1dSingle
  end function
end interface
```

2.3.6 Simpler minloc

The fortran routine minloc(array) returns the indices at which the minimum value in array occurs. However the return must be a vector quantity of the same size as the array has dimensions. This can be slightly clunky if array is of dimension 1 - ie, a 1-dimensional vector. The function minLoc1d allows one to obtain the index of the minimum value of the 1-D argument in a scalar return value. This can save some lines of code.

```
interface minLoc1d
  function minLoc1dSingle(vector, mask)
    real(single), intent(in) :: vector(:)
    logical(bool), intent(in), optional :: mask(:)
    integer :: minLoc1dSingle
  end function

  function minLoc1dDouble(vector, mask)
    real(double), intent(in) :: vector(:)
    logical(bool), intent(in), optional :: mask(:)
    integer :: minLoc1dSingle
  end function
end interface
```

2.4 Array or vector → scalar reals

2.4.1 1-D interpolation


Given a set of piecewise-continuous line segments defined by set of x values (these must be monotonically increasing) and a corresponding set of y values, and given also a single $xSample$ value, this subroutine performs a linear interpolation to return the associated $ySample$ value. If $xSample$ is outside the range of x values, or in other pathological cases, 0 is returned.

```
function linearInterpolate(x, y, xSample) result(ySample)
  real(single), intent(in) :: x(:), y(size(x)), xSample
  real(single) :: ySample
end function linearInterpolate
```

2.4.2 Trapezoid-rule, 1-D, numerical integral

Given two vectors x and y containing samples of a function F , this subroutine returns the ‘trapezoidal-rule’ estimate of the integral of F . In other words, F is replaced by the set of piecewise-continuous line segments defined by x and y . Note that x is assumed to be monotonically increasing - if it isn’t, you’ll get strange results.

```
interface trapezoidSum
```



```
function trapezoidSumSingle(x, y) result(summ)
    real(single), intent(in) :: x(:, ), y(size(x))
    real(single)           :: summ
end function trapezoidSumSingle

function trapezoidSumDouble(x, y) result(summ)
    real(double), intent(in) :: x(:, ), y(size(x))
    real(double)           :: summ
end function trapezoidSumDouble
end interface
```

2.4.3 Median

This function calculates the median value of the supplied 1- or 2-d array. The function sorts the array values: if the number of elements is odd, the central element of the sorted list is returned; if even, the element in the lower of the two central elements is returned.

```
interface median
    real(single) function medianVector(array)
        real(single), intent(in) :: vector(:)
    end function medianVector

    real(single) function medianArray(array)
        real(single), intent(in) :: array(:, :)
    end function medianArray
end interface
```

2.4.4 Value at histogram fraction

For *binFraction* = 0.5 this gives the same result as median(). The algorithm is as follows: the values in *vector* or *array* are sorted; that element index is identified which, expressed as a fraction of the total number of elements, comes nearest to *binFraction*; finally, the element which occurs at that index of the sorted list is returned.


If *binFraction* is outside the range 0 to 1, the smallest or largest element, whichever is appropriate, is returned.

```
interface valueAtHistoFraction
    real(single) function valueAtHistoFractionVector(vector, binFraction&
        , maskVector)

        real(single), intent(in)           :: vector(:), binFraction
        logical(bool), intent(in), optional :: maskVector(:)
    end function valueAtHistoFractionVector

    real(single) function valueAtHistoFractionArray(array, binFraction&
        , maskArray)

        real(single), intent(in)           :: array(:, :), binFraction
        logical(bool), intent(in), optional :: maskArray(:, :)
    end function valueAtHistoFractionArray
```



```
end interface
```

2.4.5 sumInt32Dbl

The Fortran90 builtin function `sum()` returns the value in as the same type as its argument (at least in NAG Fortran specification). For example, when `aryInt8` is an array of `Integer(int8)`, the returned value of `sum(aryInt8)` is also `Integer(int8)` — which is practically not very useful, as the total sum of `aryInt8` is very likely to exceed the maximum (or minimum if negative) possible number of `Integer(int8)` (which can be obtained with `huge()` function).


This subroutine is developed to avoid that problem; it still returns the total sum of the array as `sum()` does, but always returns the type `Integer(int32)` and/or `Real(double)` if requested, whether the type of the argument is `int8/16/32`. In addition if an overflow happens during the calculation, that is, if the absolute value of the total sum is larger than `huge(int32_variable)`, the returned `Integer(int32)` are `INTEGER_NULL`, which is defined in DAL. Also if the size of the given array is zero, the returned values are `INTEGER_NULL` and `REAL_NULL`.

`sumInt32Dbl()` can accept up to 4-dimensional arrays at the time of writing.

See also Section 2.4.6 for the handier, function version of this routine `sumInt32()`.

```
interface sumInt32Dbl
    subroutine sumInt32DblInt81d(ary, sumInInt32, sumInDbl)
        integer(int8), intent(in) :: ary(:)
        integer(int32), intent(out), optional :: sumInInt32
        real(double), intent(out), optional :: sumInDbl
    end subroutine sumInt32DblInt81d
    subroutine sumInt32DblInt161d(ary, sumInInt32, sumInDbl)
        integer(int16), intent(in) :: ary(:)
        integer(int32), intent(out), optional :: sumInInt32
        real(double), intent(out), optional :: sumInDbl
    end subroutine sumInt32DblInt161d
    subroutine sumInt32DblInt321d(ary, sumInInt32, sumInDbl)
        integer(int32), intent(in) :: ary(:)
        integer(int32), intent(out), optional :: sumInInt32
        real(double), intent(out), optional :: sumInDbl
    end subroutine sumInt32DblInt321d

    subroutine sumInt32DblInt82d(ary, sumInInt32, sumInDbl)
        integer(int8), intent(in) :: ary(:, :)
        integer(int32), intent(out), optional :: sumInInt32
    end subroutine sumInt32DblInt82d
    subroutine sumInt32DblInt162d(ary, sumInInt32, sumInDbl)
        integer(int16), intent(in) :: ary(:, :)
        integer(int32), intent(out), optional :: sumInInt32
        real(double), intent(out), optional :: sumInDbl
    end subroutine sumInt32DblInt162d
    subroutine sumInt32DblInt322d(ary, sumInInt32, sumInDbl)
        integer(int32), intent(in) :: ary(:, :)
        integer(int32), intent(out), optional :: sumInInt32
        real(double), intent(out), optional :: sumInDbl
    end subroutine sumInt32DblInt322d
```



```
subroutine sumInt32Db1Int83d(ary, sumInInt32, sumInDbl)
    integer(int8), intent(in) :: ary(:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int83d
subroutine sumInt32Db1Int163d(ary, sumInInt32, sumInDbl)
    integer(int16), intent(in) :: ary(:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int163d
subroutine sumInt32Db1Int323d(ary, sumInInt32, sumInDbl)
    integer(int32), intent(in) :: ary(:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int323d

subroutine sumInt32Db1Int84d(ary, sumInInt32, sumInDbl)
    integer(int8), intent(in) :: ary(:,:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int84d
subroutine sumInt32Db1Int164d(ary, sumInInt32, sumInDbl)
    integer(int16), intent(in) :: ary(:,:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int164d
subroutine sumInt32Db1Int324d(ary, sumInInt32, sumInDbl)
    integer(int32), intent(in) :: ary(:,:,:,:)
    integer(int32), intent(out), optional :: sumInInt32
    real(double), intent(out), optional :: sumInDbl
end subroutine sumInt32Db1Int324d
end interface
```

2.4.6 sumInt32

See Section 2.4.5 (`sumInt32Db1`) for detail. This routine is the front-end of that, namely the function version, just like the Fortran90 builtin function `sum()` but returns always Integer(int32).

Note that if the returned value is INTEGER_NULL, the caller side then can execute `sum(real(ary, double))` in order to get the total sum, in the double-precision float number this time.

```
interface sumInt32
    integer(int32) function sumInt32Int81d(ary)
        integer(int8), intent(in) :: ary(:)
    end function sumInt32Int81d
    integer(int32) function sumInt32Int82d(ary)
        integer(int8), intent(in) :: ary(:,:)
    end function sumInt32Int82d
    integer(int32) function sumInt32Int83d(ary)
        integer(int8), intent(in) :: ary(:,:,:)
    end function sumInt32Int83d
    integer(int32) function sumInt32Int84d(ary)
        integer(int8), intent(in) :: ary(:,:,:,:)
    end function sumInt32Int84d
```



```
end function sumInt32Int84d

integer(int32) function sumInt32Int161d(ary)
    integer(int16), intent(in) :: ary(:)
end function sumInt32Int161d
integer(int32) function sumInt32Int162d(ary)
    integer(int16), intent(in) :: ary(:,:,:)
end function sumInt32Int162d
integer(int32) function sumInt32Int163d(ary)
    integer(int16), intent(in) :: ary(:,:,:,:)
end function sumInt32Int163d
integer(int32) function sumInt32Int164d(ary)
    integer(int16), intent(in) :: ary(:,:,:,:,:)
end function sumInt32Int164d

integer(int32) function sumInt32Int321d(ary)
    integer(int32), intent(in) :: ary(:)
end function sumInt32Int321d
integer(int32) function sumInt32Int322d(ary)
    integer(int32), intent(in) :: ary(:,:,:)
end function sumInt32Int322d
integer(int32) function sumInt32Int323d(ary)
    integer(int32), intent(in) :: ary(:,:,:,:)
end function sumInt32Int323d
integer(int32) function sumInt32Int324d(ary)
    integer(int32), intent(in) :: ary(:,:,:,:,:)
end function sumInt32Int324d
end interface
```

2.5 Array or vector → array or vector

2.5.1 vectorCross

Performs a vector cross product.

```
interface vectorCross
    function vectorCrossSingle(vectorA, vectorB)
        real(single), intent(in) :: vectorA(3), vectorB(3)
        real(single)           :: vectorCrossSingle(3)
    end function vectorCrossSingle

    function vectorCrossDouble(vectorA, vectorB)
        real(double), intent(in) :: vectorA(3), vectorB(3)
        real(double)           :: vectorCrossDouble(3)
    end function vectorCrossDouble
end interface
```

2.5.2 normalizeVector

Given argument \bar{v} returns \hat{v} .



```
interface normalizeVector
    function normalizeVectorSingle(argument)
        real(single), intent(in) :: argument(:)
        real(single) :: normalizeVectorSingle(size(argument))
    end function normalizeVectorSingle

    function normalizeVectorDouble(argument)
        real(double), intent(in) :: argument(:)
        real(double) :: normalizeVectorDouble(size(argument))
    end function normalizeVectorDouble
end interface
```

2.5.3 findEdges

```
subroutine findEdges(mask, figureEdges, groundEdges)
    logical(bool), intent(in) :: mask(:, :)
    logical(bool), intent(out), optional ::&
        figureEdges(size(mask, 1), size(mask, 2)), &
        groundEdges(size(mask, 1), size(mask, 2))
end subroutine findEdges
```

Given an input logical array *mask*, this subroutine returns (optionally) an array *figureEdges* which is true at all true-valued pixels in *mask* which have at least 1 false-valued pixel among their 8 nearest neighbours. (For pixels at the edges of the input array, the number of nearest neighbours is of course reduced to 5 or 3 as appropriate.)

I give an example as follows, in which false pixels are represented by 0 and true by 1. For an input mask

```
11110000111
1111000011
11111100011
11111100001
000000000000
11111110000
11101111100
```

the returned *figureEdges* should be

```
00010000110
00011000010
00001100011
11111100001
000000000000
11111110000
00101011100
```

A second array *groundEdges* is also optionally returned, which is equivalent to *figureEdges* calculated for *.not.mask*.



2.5.4 invertMask

This subroutine inverts the 2-d or 3-d input mask array, which is either Logical, Logical(bool) or Integer(int8), where .true. and .false. are 1 and 0, respectively.

```
interface invertMask
    subroutine invertMask2dLogical(mask)
        logical, intent(inout) :: mask(:,:)
    end subroutine invertMask2dLogical

    subroutine invertMask2dBool(mask)
        logical(bool), intent(inout) :: mask(:,:)
    end subroutine invertMask2dBool

    subroutine invertMask2dInt8(mask)
        integer(int8), intent(inout) :: mask(:,:)
    end subroutine invertMask2dInt8

    subroutine invertMask3dLogical(mask)
        logical, intent(inout) :: mask(:,:,:)
    end subroutine invertMask3dLogical

    subroutine invertMask3dBool(mask)
        logical(bool), intent(inout) :: mask(:,:,:)
    end subroutine invertMask3dBool

    subroutine invertMask3dInt8(mask)
        integer(int8), intent(inout) :: mask(:,:,:)
    end subroutine invertMask3dInt8
end interface
```

2.6 Array or vector → other

2.6.1 getAryStatInfo


This function returns the structure `aryStatInfo???`T (See Section 2.2), which contains the statistical information of the array. This function offers an interface for five (numerical) types of input Array and the type of the returned value (`aryStatInfo???`T) varies accordingly.

At the time of writing (ssclib-4.6), it accepts the 1- and 2-dimensional arrays. In the future it is planned to accept 3-dimensional arrays as well.

The following is an example interface for the Double-type one. In other types, only the difference is the type of the input Array, `arin` (and the returned type, accordingly – see Section 2.2 for detail).

```
interface getAryStatInfo
    function getAryStatInfoDouble1d(arin, arMaskIn &
        , minAreaIndices, maxAreaIndices, valLower, valUpper, flagInfo) result(retInfo)

        integer, parameter :: rankArin = 1
        type(aryStatInfoDoubleT) :: retInfo
```



```
real(double), intent(in) :: arin(:)
logical, intent(in), optional :: arMaskIn(:)
integer(int32), intent(in), optional :: minAreaIndices(rankArin), maxAreaIndices(rankArin)
real(double), intent(in), optional :: valLower, valUpper
type(aryStatInfoFlagT), intent(in), optional :: flagInfo
end function getAryStatInfoDouble1d

function getAryStatInfoDouble2d(arin, arMaskIn &
, minAreaIndices, maxAreaIndices, valLower, valUpper, flagInfo) result(retInfo)

integer, parameter :: rankArin = 2
type(aryStatInfoDoubleT) :: retInfo
real(double), intent(in) :: arin(:,:) ! Input data Array
logical, intent(in), optional :: arMaskIn(:,:)
integer(int32), intent(in), optional :: minAreaIndices(rankArin), maxAreaIndices(rankArin)
real(double), intent(in), optional :: valLower, valUpper
type(aryStatInfoFlagT), intent(in), optional :: flagInfo
end function getAryStatInfoDouble2d
end interface
```

Note that the ranks of arin and arMaskIn (if specified) have to be identical.

2.6.2 calcAryStatInfoMask

This subroutine is the core routine for the function `getAryStatInfo` (Section 2.6.1). The difference is that this function returns, as well as (`aryStatInfo????T`), the final mask file, which is used to determine the valid entry to calculate the statistical information of the array. If that is what you want, you can call this subroutine directly.


The following is an example interface for the Double-type one. Again, in other types, only the difference is the type of the input Array, `arin` (and the returned type, accordingly – see Section 2.2 for detail).

```
interface calcAryStatInfoMask
    subroutine calcAryStatInfoMaskDouble1d(arin, retInfo, arMaskOut, arMaskIn &
, minAreaIndices, maxAreaIndices, valLower, valUpper, flagInfo)

        integer, parameter :: rankArin = 1
        real(double), intent(in) :: arin(:) ! Input data Array
        type(aryStatInfoDoubleT), intent(out) :: retInfo
        logical, intent(out) :: arMaskOut(:) ! Must be predefined.
        logical, intent(in), optional :: arMaskIn(:)
        integer(int32), intent(in), optional :: minAreaIndices(rankArin), maxAreaIndices(rankArin)
        real(double), intent(in), optional :: valLower, valUpper
        type(aryStatInfoFlagT), intent(in), optional :: flagInfo
    end subroutine calcAryStatInfoMaskDouble1d

    subroutine calcAryStatInfoMaskDouble2d(arin, retInfo, arMaskOut, arMaskIn &
, minAreaIndices, maxAreaIndices, valLower, valUpper, flagInfo)

        integer, parameter :: rankArin = 2
        real(double), intent(in) :: arin(:,:) ! Input data Array
        type(aryStatInfoDoubleT), intent(out) :: retInfo
        logical, intent(out) :: arMaskOut(:,:) ! Must be predefined.
```



```
logical, intent(in), optional :: arMaskIn(:,:)
integer(int32), intent(in), optional :: minAreaIndices(rankArin), maxAreaIndices(rankArin)
real(double), intent(in), optional :: valLower, valUpper
type(aryStatInfoFlagT), intent(in), optional :: flagInfo
end subroutine calcAryStatInfoMaskDouble2d
end interface
```

Note that the ranks of arin and arMaskIn (if specified) and arMaskOut have to be identical. And (the rank of) arMaskOut has to be defined in the caller side before the call.

2.6.3 printAryStatInfo

Print the contents of aryStatInfo???T structure variable to STDOUT. Note that some of the values are not printed if undefined. This returns nothing.

```
interface printAryStatInfo
    subroutine printAryStatInfoDouble(aryInfo)
        type(aryStatInfo???T), intent(in) :: aryInfo
    end subroutine printAryStatInfoDouble
end interface
```

3 Subroutine shortcuts for manipulating information used for setting the CAL state

Module name: cal_aux

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

3.1 Extract information about the instrument, exposure start time and space-craft and instrument attitude from a dataset header.

```
interface getCalInfo
    subroutine getCalInfoName(setName, instrumentId, expStartTimeStamp&
        , scAttitude, instrumAttitude)

        character(*),           intent(in)  :: setName
        integer(int32),         intent(out) :: instrumentId
        real(double),           intent(out) :: expStartTimeStamp
        type(SpacecraftAttitudeType), intent(out) :: scAttitude, instrumAttitude
    end subroutine getCalInfoName

    subroutine getCalInfoSet(set, instrumentId, expStartTimeStamp, scAttitude&
        , instrumAttitude)

        type(DataSetT),          intent(in)  :: set
        integer(int32),           intent(out) :: instrumentId
        real(double),             intent(out) :: expStartTimeStamp
    end subroutine getCalInfoSet
```



```
    type(SpacecraftAttitudeType), intent(out) :: scAttitude, instrumAttitude
  end subroutine getCalInfoSet
end interface
```

NOTE that this call also sets the state of the **cal** to the returned instrument.

The *instrumentId* and *expStartTimeStamp* are obtained from respectively from the INSTRUME and DATE-OBS keywords of the dataset header. The *scAttitude* is read from the RA_PNT, DEC_PNT and PA_PNT keywords (this is actually wrong, since the *instrument* attitude is what should be stored in these, not the spacecraft attitude). The boresight is then obtained for the exposure start time, and *instrumAttitude* calculated by applying the boresight rotation to *scAttitude*.

3.2 Spacecraft → instrument attitude

```
function getInstrumentAttitude(scAttitude, timeStamp) result(instrumAttitude)
  real(double),           intent(in) :: timeStamp
  type(SpacecraftAttitudeType), intent(in) :: scAttitude
  type(SpacecraftAttitudeType)           :: instrumAttitude
end function getInstrumentAttitude
```

NOTE this function requires the **cal** to have been set to the correct instrument before the call.

3.3 Instrument → spacecraft attitude

```
function getScAttitude(instrumAttitude, timeStamp) result(scAttitude)
  real(double),           intent(in) :: timeStamp
  type(SpacecraftAttitudeType), intent(in) :: instrumAttitude
  type(SpacecraftAttitudeType)           :: scAttitude
end function getScAttitude
```

NOTE this function requires the **cal** to have been set to the correct instrument before the call.

4 Routines to calculate source confusion

Module name: **confusion**

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

```
subroutine findConfusedSets(srcX, srcY, srcRadius, confSetNum)
  real(double), intent(in) :: srcX(:), srcY(size(srcX))
  real(double), intent(in) :: srcRadius(size(srcX))
  integer(int16), intent(out) :: confSetNum(size(srcX))
end subroutine findConfusedSets
```

This subroutine takes as inputs a list of source positions \$srcX\$ and \$srcY\$ and nominal radii \$src

There are no gaps in the returned sequence of confusion indices. Ie for all valid confusion indices



5 A module which contains various mathematical and physical constants

Module name: `constants`

Authors: Richard West (University of Leicester, rgw@star.le.ac.uk), Ian Stewart (University of Leicester, ims@star.le.ac.uk).

5.1 Constants

The `constants` module defines a set of widely used mathematical and physical constants. The constants are defined as “double precision” (`real (kind=double)`).

5.1.1 Pi-related constants

Name	Value	Description
Pi	3.1415926535897931	π
TwoPi	2.0*Pi	2π
FourPi	4.0*Pi	4π
PiOverTwo	0.5*Pi	$\pi/2$
PiOn2	0.5*Pi	$\pi/2$
OneOverPi	1.0/Pi	$1/\pi$
OneOverTwoPi	0.5/Pi	$1/2\pi$

5.1.2 Angle conversion factors

Name	Value	Description
DegToRad	TwoPi/360.0	Degrees to radians
RadToDeg	360.0/TwoPi	Radians to degrees
Deg2Rad	TwoPi/360.0	Degrees to radians
PiOn180	TwoPi/360.0	Degrees to radians
ArcminToRad	DegToRad/60.0	Arcminutes to radians
RadToArcmin	RadToDeg*60.0	Radians to arcminutes
ArcsecToRad	DegToRad/3600.0	Arcseconds to radians
RadToArcsec	RadToDeg*3600.0	Radians to arcseconds

5.1.3 Solid angle conversion factors

Name	Value	Description
SqDegToSterad	DegToRad ²	Square degrees to steradian
SqArcminToSterad	SqDegToSterad/3600.0	Square arcminutes to steradians
SqArcsecToSterad	SqDegToSterad/1.296 × 10 ⁷	Square arcseconds to steradian
SteradToSqDeg	RadToDeg ²	Steradian to square degrees
SteradToSqArcmin	SteradToSqDeg*3600.0	Steradian to square arcminutes
SteradToSqArcsec	SteradToSqDeg*1.296 × 10 ⁷	Steradian to square arcseconds



5.1.4 Square roots

Name	Value	Description
RootTwo	1.4142135623730951	$\sqrt{2}$
RootThree	1.7320508075688772	$\sqrt{3}$
RootTen	3.1622776601683795	$\sqrt{10}$
RootPi	1.7724538509055159	$\sqrt{\pi}$

5.1.5 Natural log-related

Name	Value	Description
NapierE	2.7182818284590455	e
lnTwo	0.6931471805599453	$\ln 2$
lnThree	1.0986122886681098	$\ln 3$
lnFive	1.6094379124341003	$\ln 5$
lnSeven	1.9459101490553132	$\ln 7$
lnTen	2.3025850929940459	$\ln 10$
lnPi	1.1447298858494002	$\ln \pi$

5.1.6 Fundamental physical constants

Name	Value	Description
SpeedOfLight	299792458.0	c (m s^{-1})
PlanckH	$6.62606876 \times 10^{-34}$	h (J s)
NewtonG	6.673×10^{-11}	G ($\text{m}^3 \text{ kg}^{-1} \text{ s}^{-2}$)
ElectronQ	$1.602176462 \times 10^{-19}$	e (C)
Boltzmann	$1.3806503 \times 10^{-23}$	k (J K^{-1})
StefanBoltzmann	5.670400×10^{-8}	σ ($\text{W m}^{-2} \text{ K}^{-4}$)
Avogadro	$6.02214199 \times 10^{23}$	N_A (mol^{-1})

5.1.7 Energy conversion factors


Name	Value	Description
ErgToeV	1.0d-7 / ElectronQ	erg to eV
ErgTokeV	ErgToeV/1000.0	erg to keV
eVToErg	1.0/ErgToeV	eV to ergs
keVToErg	1000.0/ErgToeV	keV to ergs

5.1.8 Solar system constants

Name	Value	Description
EarthRadius	6378.14	km

5.2 Unit conversion routines

```
function angstroms2eV(angstroms) result(EeV)
```



```
real(double), intent(in) :: angstroms
real(double)           :: EeV
end function angstroms2eV

function eV2angstroms(EeV) result(angstroms)
real(double), intent(in) :: EeV
real(double)           :: angstroms
end function eV2angstroms
```

5.3 Black Body routines

These subroutines calculate the power (in watts) radiated per unit surface area (m^2) per unit solid angle (sr) by a black body at temperature='kelvin'. The power can be calculated either per unit frequency, at a given frequency (both in hertz), or per unit wavelength (in metres) at a given supplied wavelength (in angstroms).

The subroutines are designed to be portable and as fast yet as accurate as possible.

5.3.1 Per unit frequency

The precision at low frequencies f is limited by the calculation of $\exp(x)-1$, where $x = hfk/T$. At low values of x, $\exp(x)$ is close to 1 and thus the difference between $\exp(x)$ and 1 is a number of low precision. Thus for x values less than 0.1, a series expansion of $(\exp(x)-1)/x$ is used instead. The minimum precision occurs at x = 0.1 and is approximately equal to precision(1d0)-1.

```
subroutine getBBfluxPerHertz(hertzValues, kelvin, powerValues)
real(double), intent(in) :: hertzValues(:), kelvin
real(double), intent(out) :: powerValues(size(hertzValues))
end subroutine getBBfluxPerHertz

function bbFluxPerHertz(hertz, kelvin) result(power)
real(double), intent(in) :: hertz, kelvin
real(double)           :: power
end function bbFluxPerHertz
```

5.3.2 Per unit wavelength

The precision at long wavelengths L is limited by the calculation of $\exp(x)-1$, where $x = hL/TL$. At low values of x, $\exp(x)$ is close to 1 and thus the difference between $\exp(x)$ and 1 is a number of low precision. Thus for x values less than 0.1, a series expansion of $(\exp(x)-1)/x$ is used instead. The minimum precision occurs at x = 0.1 and is approximately equal to precision(1d0)-1.

```
subroutine getBBfluxPerMetre(angstromValues, kelvin, powerValues)
real(double), intent(in) :: angstromValues(:), kelvin
real(double), intent(out) :: powerValues(size(angstromValues))
end subroutine getBBfluxPerMetre

function bbFluxPerMetre(angstroms, kelvin) result(power)
real(double), intent(in) :: angstroms, kelvin
```



```
    real(double)      :: power
end function bbFluxPerMetre
```

6 Routines for performing coordinate transforms

**** include changes in version 3.6.5 etc

Module name: **coordinate**

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

This module contains subroutines to perform a variety of coordinate transformations. Where possible the **cal** coordinate-transformation routines are used. The present subroutines have been designed to act as wrappers-of-convenience for one or more of the **cal** routines rather than to supplant them.

6.1 getPsfImagePixelCorners

```
subroutine getPsfImagePixelCorners(psfThetaArcsec, psfPhi, psfPixelSizeMm&
, psfImage, wcs, wcsType, instrumentId, timeStamp, scAttitude&
, psfImagePixelCorners, psfCentrePixels)

real(double),           intent(in)  :: psfThetaArcsec, psfPhi
type(PsfBinSizeT),      intent(in)  :: psfPixelSizeMm
real(single),           intent(in)  :: psfImage(:, :)
type(WcsT),             intent(in)  :: wcs
character(*),           intent(in)  :: wcsType
integer(int32),          intent(in)  :: instrumentId
real(double),           intent(in)  :: timeStamp
type(SpacecraftAttitudeType), intent(in)  :: scAttitude
type(Point2dT),          intent(out) :: psfImagePixelCorners(&
                                         size(psfImage,1)+1&
                                         ,size(psfImage,2)+1)
type(Point2dT),          intent(out) :: psfCentrePixels
end subroutine getPsfImagePixelCorners
```

This subroutine takes an image of the Point Spread Function (PSF) returned by the **cal** call CAL_getPsfImage for a given instrument and returns an array of *x* and *y* coordinates, in the sky image coordinate system defined by the *wcs* structure *wcs*, of the intersections of the pixel edge grid of this image. This grid intersections array is necessary as input to the routine regrid (see section ??), the purpose of which is to rebin the PSF image to sky coordinates.

NOTE this subroutine requires the **cal** to have been set to the correct instrument before the call.

6.2 raDecToInst

```
interface raDecToInst
    subroutine raDecToInstScalar(raDeg, decDeg, scAttitude&
        , timeStamp, detX, detY, thetaArcsec, phi)
```



```
    real(double),           intent(in) :: raDeg,&
                                         decDeg
    type(SpacecraftAttitudeType), intent(in) :: scAttitude
    real(double),           intent(in) :: timeStamp
    real(single)      , optional, intent(out) :: detX,&
                                         detY
    real(double)      , optional, intent(out) :: thetaArcsec,&
                                         phi
end subroutine raDecToInstScalar

subroutine raDecToInstVector(raDeg, decDeg, scAttitude&
, timeStamp, detX, detY, thetaArcsec, phi)

    real(double),           intent(in) :: raDeg(:),&
                                         decDeg(size(raDeg))
    type(SpacecraftAttitudeType), intent(in) :: scAttitude
    real(double),           intent(in) :: timeStamp
    real(single)      , optional, intent(out) :: detX(size(raDeg)),&
                                         detY(size(raDeg))
    real(double)      , optional, intent(out) :: thetaArcsec(size(raDeg)),&
                                         phi(size(raDeg))
end subroutine raDecToInstVector

! raDecToInstArray not yet done

end interface
```

This subroutine converts from celestial coordinates to instrument-centric coordinates, in either the DETX/Y (the same, up to a scalar multiple, as the CAMCOORD2 system) or TELCOORD systems, depending on which of the optional variables *detX*, *detY*, *thetaArcsec* and *phi* the caller has supplied.

NOTE this subroutine requires the **cal** to have been set to the correct instrument before the call.


6.3 instToRaDec

```
interface instToRaDec
    subroutine instToRaDecScalar(raDeg, decDeg, scAttitude&
, timeStamp, detX, detY, thetaArcsec, phi)

        real(double),           intent(out) :: raDeg,&
                                         decDeg
        type(SpacecraftAttitudeType), intent(in) :: scAttitude
        real(double),           intent(in) :: timeStamp
        real(single),      optional, intent(in) :: detX,&
                                         detY
        real(double),      optional, intent(in) :: thetaArcsec,&
                                         phi
    end subroutine instToRaDecScalar

    subroutine instToRaDecVector(raDeg, decDeg, scAttitude&
, timeStamp, detX, detY, thetaArcsec, phi)

        real(double),           intent(out) :: raDeg(:),&
```



```
          decDeg(size(raDeg))
type(SpacecraftAttitudeType), intent(in) :: scAttitude
real(double),           intent(in)   :: timeStamp
real(single),    optional, intent(in)   :: detX(size(raDeg)),&
                                         detY(size(raDeg))
real(double),    optional, intent(in)   :: thetaArcsec(size(raDeg)),&
                                         phi(size(raDeg))
end subroutine instToRaDecVector

! instToRaDecArray not yet done

end interface
```

This subroutine converts to celestial coordinates from instrument-centric coordinates, in either the DETX/Y (the same, up to a scalar multiple, as the CAMCOORD2 system) or TELCOORD systems, depending on which of the optional variables *detX*, *detY*, *thetaArcsec* and *phi* the caller has supplied.

NOTE this function requires the **cal** to have been set to the correct instrument before the call.

6.4 raDecToTan


```
interface raDecToTan
  subroutine raDecToTanScalar(refRaDeg, refDecDeg, raDeg, decDeg, tanX, tanY)
    real(double), intent(in)  :: refRaDeg,&
                                refDecDeg,&
                                raDeg,&
                                decDeg
    real(double), intent(out) :: tanX,&
                                tanY
  end subroutine raDecToTanScalar

  subroutine raDecToTanVector(refRaDeg, refDecDeg, raDeg, decDeg, tanX, tanY)
    real(double), intent(in)  :: refRaDeg,&
                                refDecDeg,&
                                raDeg(:),&
                                decDeg(size(raDeg))
    real(double), intent(out) :: tanX(size(raDeg)),&
                                tanY(size(raDeg))
  end subroutine raDecToTanVector

! raDecToTanArray not yet done

end interface
```

This transform is a projection from celestial coordinates to that tangent plane normal to the direction defined by *refRaDeg* and *refDecDeg*. The signs of the the returned values are such that *tanX* increases in the direction of decreasing *ra* and *tanY* increases in the direction of increasing *dec*. If the tangent plane were viewed from the centre of the celestial sphere, with the celestial north pole at the zenith, *tanX* would increase to rightwards and *tanY* upwards.



6.5 tanToRaDec

```
interface tanToRaDec
    subroutine tanToRaDecScalar(refRaDeg, refDecDeg, tanX, tanY, raDeg, decDeg)
        real(double), intent(in) :: refRaDeg,&
                                    refDecDeg,&
                                    tanX,&
                                    tanY
        real(double), intent(out) :: raDeg,&
                                    decDeg
    end subroutine tanToRaDecScalar

    subroutine tanToRaDecVector(refRaDeg, refDecDeg, tanX, tanY, raDeg, decDeg)
        real(double), intent(in) :: refRaDeg,&
                                    refDecDeg,&
                                    tanX(:),&
                                    tanY(size(tanX))
        real(double), intent(out) :: raDeg(size(tanX)),&
                                    decDeg(size(tanX))
    end subroutine tanToRaDecVector
end interface

! tanToRaDecArray not yet done
```


This transform is a projection to celestial coordinates from that tangent plane normal to the direction defined by refRaDeg and refDecDeg. The signs of the the returned values are such that tanX increases in the direction of decreasing ra and tanY increases in the direction of increasing dec. If the tangent plane were viewed from the centre of the celestial sphere, with the celestial north pole at the zenith, tanX would increase to rightwards and tanY upwards.

6.6 polarsToRaDec

```
interface polarsToRaDec
    subroutine polarsToRaDecVector(refRaDeg, refDecDeg, theta, phi, raDeg&
        , decDeg)
        real(double), intent(in) :: refRaDeg,&
                                    refDecDeg,&
                                    theta(:),&
                                    phi(size(theta))
        real(double), intent(out) :: raDeg(size(theta)),&
                                    decDeg(size(theta))
    end subroutine polarsToRaDecVector
end interface

! tanToRaDecScalar, tanToRaDecArray not yet done
```

The same as tanToRaDec (section ??), except the coordinates on the tangent plane are now given in polar coordinates *theta* and *phi* instead of cartesian *tanX* and *tanY*. The relationship between the two sets is as follows:



$$\tan X = \tan(\theta) \cos(\phi) \quad \tan Y = \tan(\theta) \sin(\phi)$$

6.7 instToTan


```

interface instToTan
  subroutine instToTanScalar(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)
    real(double), intent(out) :: tanX,&
                                tanY
    real(double), intent(in)  :: refRaDeg,&
                                refDecDeg
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double), intent(in)  :: timeStamp
    real(single), optional, intent(in)  :: detX,&
                                detY
    real(double), optional, intent(in)  :: thetaArcsec,&
                                phi
  end subroutine instToTanScalar

  subroutine instToTanVector(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)
    real(double), intent(out) :: tanX(:,&
                                tanY(size(tanX)))
    real(double), intent(in)  :: refRaDeg,&
                                refDecDeg
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double), intent(in)  :: timeStamp
    real(single), optional, intent(in)  :: detX(size(tanX)),&
                                detY(size(tanX))
    real(double), optional, intent(in)  :: thetaArcsec(size(tanX)),&
                                phi(size(tanX))
  end subroutine instToTanVector

  subroutine instToTanArray(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)
    real(double), intent(out) :: tanX(:,:,&
                                tanY(size(tanX,1),&
                                size(tanX,2)))
    real(double), intent(in)  :: refRaDeg,&
                                refDecDeg
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double), intent(in)  :: timeStamp
    real(single), optional, intent(in)  :: detX(size(tanX,1),&
                                size(tanX,2)),&
                                detY(size(tanX,1),&
                                size(tanX,2))
    real(double), optional, intent(in)  :: thetaArcsec(size(tanX,1),&
                                size(tanX,2)),&
                                phi(size(tanX,1),&
                                size(tanX,2))
  end subroutine instToTanArray

```



```
    end subroutine instToTanArray  
end interface
```

Effectively this is just `instToRaDec` (section ??) followed by `raDecToTan` (section ??).

NOTE this function requires the **cal** to have been set to the correct instrument before the call.

6.8 tanToInst

```

interface tanToInst

  subroutine tanToInstScalar(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)

    real(double),           intent(in)  :: refRaDeg,&
                                         refDecDeg,&
                                         tanX,&
                                         tanY
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double),           intent(in)  :: timeStamp
    real(single),          optional, intent(out) :: detX,&
                                                 detY
    real(double),          optional, intent(out) :: thetaArcsec,&
                                                 phi
  end subroutine tanToInstScalar


  subroutine tanToInstVector(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)

    real(double),           intent(in)  :: refRaDeg,&
                                         refDecDeg,&
                                         tanX(:),&
                                         tanY(size(tanX))
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double),           intent(in)  :: timeStamp
    real(single),          optional, intent(out) :: detX(size(tanX)),&
                                                 detY(size(tanX))
    real(double),          optional, intent(out) :: thetaArcsec(size(tanX)),&
                                                 phi(size(tanX))
  end subroutine tanToInstVector

  subroutine tanToInstArray(tanX, tanY, refRaDeg, refDecDeg, scAttitude&
    , timeStamp, detX, detY, thetaArcsec, phi)

    real(double),           intent(in)  :: refRaDeg,&
                                         refDecDeg,&
                                         tanX(:,:,&
                                         tanY(size(tanX,1),&
                                         size(tanX,2))
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double),           intent(in)  :: timeStamp
    real(single),          optional, intent(out) :: detX(size(tanX,1),&
                                                 size(tanX,2)),&
                                                 size(tanX,2))
  end subroutine tanToInstArray

```



```
detY(size(tanX,1),&
      size(tanX,2))
real(double),      optional, intent(out) :: thetaArcsec(size(tanX,1),&
                                                       size(tanX,2)),&
                                               phi(size(tanX,1),&
                                                size(tanX,2))

end subroutine tanToInstArray
end interface
```

Effectively this is just tanToRaDec (section ??) followed by raDecToInst (section ??).

NOTE this function requires the **cal** to have been set to the correct instrument before the call.

6.9 instToRaw

```
interface instToRaw
    subroutine instToRawScalarInt16(rawX, rawY, detX, detY, thetaArcsec, phi)
        real(single), intent(in), optional :: detX,&
                                            detY
        real(double), intent(in), optional :: thetaArcsec,&
                                            phi
        integer(int16), intent(out)       :: rawX,&
                                            rawY
    end subroutine instToRawScalarInt16


    subroutine instToRawVectorInt16(rawX, rawY, detX, detY, thetaArcsec, phi)
        real(single), intent(in), optional :: detX(size(rawX)),&
                                            detY(size(rawX))
        real(double), intent(in), optional :: thetaArcsec(size(rawX)),&
                                            phi(size(rawX))
        integer(int16), intent(out)       :: rawX(:),&
                                            rawY(size(rawX))
    end subroutine instToRawVectorInt16

    subroutine instToRawScalarReal32(rawXreal, rawYreal, detX, detY&
                                     , thetaArcsec, phi, isOffChip)

        real(single), intent(in), optional :: detX,&
                                            detY
        real(double), intent(in), optional :: thetaArcsec,&
                                            phi
        real(single), intent(out)       :: rawXreal,&
                                            rawYreal
        logical(bool), intent(out), optional :: isOffChip
    end subroutine instToRawScalarReal32

    subroutine instToRawVectorReal32(rawXreal, rawYreal, detX, detY&
                                     , thetaArcsec, phi, isOffChip)

        real(single), intent(in), optional :: detX(size(rawXreal)),&
                                            detY(size(rawXreal))
        real(double), intent(in), optional :: thetaArcsec(size(rawXreal)),&
                                            phi(size(rawXreal))
    end subroutine instToRawVectorReal32
```



```
real(single), intent(out)          :: rawXreal(:),&
                                    rawYreal(size(rawXreal))
logical(bool), intent(out), optional :: isOffChip(size(rawXreal))
end subroutine instToRawVectorReal32
end interface
```

These subroutines convert to chip coordinates (ie, the RAWX/Y or PIXCOORD1 system) from instrument-centric coordinates, the latter being either the DETX/Y (the same, up to a scalar multiple, as the CAMCOORD2 system) or the TELCOORD system, depending on which of the optional variables *detX*, *detY*, *thetaArcsec* and *phi* the caller has supplied.

The ‘int16’ routines employ the **cal** calls CAL.camCoord1ToChipCoord and CAL.chipCoordToPixCoord1. However, these calls have two drawbacks: firstly, they return integer values, and secondly, they are only valid ‘on-chip’. However there are occasions when it is desirable to obtain finer precision in the chip coordinates and also to be able to out of the strict range. For this reason I wrote the ‘real32’ routines. The latter do not use the **cal** calls mentioned above. Instead they first move forward by calculating the instrument-centric coordinates of the corners of the CCD; this information is then used to perform a linear back-transformation of the input instrument-centric coordinates. The logical variable *isOffChip* is also set.

NOTE this subroutine requires the **cal** to have been set to the correct instrumentId, ccdChipId and (if instrumentId is EMOS1 or EMOS2) ccdNodeId before the call.

6.10 rawToInst

```
interface rawToInst
    subroutine rawToInstScalar(rawX, rawY, detX, detY, thetaArcsec, phi)
        integer(int16), intent(in)          :: rawX,&
                                              rawY
        real(double), intent(out), optional :: thetaArcsec,&
                                              phi
        real(single), intent(out), optional :: detX,&
                                              detY
    end subroutine rawToInstScalar

    subroutine rawToInstVector(rawX, rawY, detX, detY, thetaArcsec, phi)
        integer(int16), intent(in)          :: rawX(:),&
                                              rawY(size(rawX))
        real(double), intent(out), optional :: thetaArcsec(size(rawX)),&
                                              phi(size(rawX))
        real(single), intent(out), optional :: detX(size(rawX)),&
                                              detY(size(rawX))
    end subroutine rawToInstVector

    subroutine rawToInstArray(rawX, rawY, detX, detY, thetaArcsec, phi)
        integer(int16), intent(in)          :: rawX(:, :),&
                                              rawY(size(rawX,1),size(rawX,2))
        real(double), intent(out), optional :: thetaArcsec(size(rawX,1)&
                                              ,size(rawX,2)),&
                                              phi(size(rawX,1),size(rawX,2))
        real(single), intent(out), optional :: detX(size(rawX,1),size(rawX,2)),&
                                              detY(size(rawX,1),size(rawX,2))
    end subroutine rawToInstArray
```



```
end interface
```

These subroutines convert from chip coordinates (ie, the RAWX/Y or PIXCOORD1 system) to instrument-centric coordinates, the latter being either the DETX/Y (the same, up to a scalar multiple, as the CAMCOORD2 system) or the TELCOORD system, depending on which of the optional variables *detX*, *detY*, *thetaArcsec* and *phi* the caller has supplied. The **cal** calls CAL_rawXY2mm and CAL_camCoord2ToTelCoord are employed.

NOTE this function requires the **cal** to have been set to the correct instrumentId, ccdChipId and (if instrumentId is EMOS1 or EMOS2) ccdNodeId before the call.

6.11 getThetaPhiMaps

```
subroutine getThetaPhiMaps(wcs, scAttitude, timeStamp, thetaMap, phiMap)
    type(WcsT),           intent(in)  :: wcs
    type(SpacecraftAttitudeType), intent(in)  :: scAttitude
    real(double),          intent(in)  :: timeStamp
    real(double),          intent(out) :: thetaMap(:, :, &
                                              phiMap(size(thetaMap, 1)&
                                                    , size(thetaMap, 2)))
end subroutine getThetaPhiMaps
```

This subroutine returns two arrays in the sky image coordinate system defined by the WCS structure *wcs*: one containing the θ and the other the ϕ value at that pixel; θ and ϕ being the instrument-mirror-centric TELCOORD-system polar coordinates.

6.12 skyToCartesian


```
interface skyToCartesian
    function skyToCartesianSingle(ra, dec) result(vector)
        real(single), intent(in)  :: ra, dec
        real(single)             :: vector(3)
    end function skyToCartesian

    function skyToCartesianDouble(ra, dec) result(vector)
        real(double), intent(in) :: ra, dec
        real(double)            :: vector(3)
    end function skyToCartesian
end interface
```

Returns a vector of direction cosines of the celestial coordinates *ra* and *dec*. NOTE *ra* and *dec* must be in radians.

6.13 cartesianToSky

```
subroutine cartesianToSky(vector, ra, dec)
    real(double), intent(in)  :: vector(3)
    real(double), intent(out) :: ra, dec
```



```
end subroutine cartesianToSky
```

Takes a vector of direction cosines and returns the corresponding celestial coordinates *ra* and *dec*. NOTE *ra* and *dec* are in radians.

6.14 telCoordToDetXY

```
interface telCoordToDetXY
    subroutine telCoordToDetXYScalar(thetaArcsec, phi, detX, detY)
        real(double), intent(in) :: phi, thetaArcsec
        real(single), intent(out) :: detX, detY
    end subroutine telCoordToDetXYScalar

    subroutine telCoordToDetXYVector(thetaArcsec, phi, detX, detY)
        real(double), intent(in) :: phi(:), thetaArcsec(size(phi))
        real(single), intent(out) :: detX(size(phi)), detY(size(phi))
    end subroutine telCoordToDetXYVector
end interface
```

Takes a position in the TELCOORD system and returns it in DETXY (ie, in CAMCOORD2 multiplied by a factor to convert mm at the focal plane (the unit of CAMCOORD2) to units of 0.05 arcsec (the unit of DETXY)).

6.15 detXYToTelCoord

```
interface detXYToTelCoord
    module procedure detXYToTelCoordScalar
    module procedure detXYToTelCoordVector
end interface
```

Takes a position in the DETXY (ie, in CAMCOORD2 multiplied by a factor to convert mm at the focal plane (the unit of CAMCOORD2) to units of 0.05 arcsec (the unit of DETXY)) system and returns it in TELCOORD.

6.16 detXY unit definition


The coordinate module also contains the following line:

```
real(single), public, parameter :: detUnitArcsec = 0.05
```

A better place for this would arguably be in a .par file somewhere.

6.17 angleBetweenCelCoords

```
interface angleBetweenCelCoords
```



```
function angleBetweenCelCoordsSingle(vectorA, vectorB, isRadian) result(angle)
    real(single) :: angle
    real(single), intent(in) :: vectorA(2), vectorB(2)
    logical, intent(in), optional :: isRadian
end function angleBetweenCelCoordsSingle

function angleBetweenCelCoordsDouble(vectorA, vectorB, isRadian) result(angle)
    real(double) :: angle
    real(double), intent(in) :: vectorA(2), vectorB(2)
    logical, intent(in), optional :: isRadian
end function angleBetweenCelCoordsDouble
end interface angleBetweenCelCoords
```

Returns the angle between the two pair of input celestial coordinates. The default unit is radian (`isRadian` is T), but can be degree (`isRadian` is F).

7 An additional layer over the DAL which implements some short cuts

Module name: `dal_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

This module contains subroutines designed to augment the Data Access Layer routines for accessing data in FITS files (see the `dal` library). The subroutines perform some short cuts I have found useful.

7.1 splitSetTabName

```
subroutine splitSetTabName(setTabName, setName, tabName, noColonFound, useBlock)
    character(*), intent(in)          :: setTabName
    character(*), intent(out)         :: setName, tabName
    logical,      intent(out), optional :: noColonFound
    logical,      intent(in), optional :: useBlock
end subroutine splitSetTabName
```

The parameter type ‘table’ (see `param`) accepts a string consisting of a dataset name followed by a colon followed by a binary table name. If the user forgets to include the colon + table name, the resulting `dal` error is not very helpful as an indication of what has gone wrong. Personally I find it more useful to have as the default behaviour in this case that the first table in the dataset should be opened, with an accompanying warning. So I have written this routine `splitSetTabName()` to act as a trap for the situation in which the user leaves off the colon+table name. The idea is that the string read from a ‘table’-type parameter is sent first to `splitSetTabName()`, which searches the string for a colon; if it finds one, then it returns the before- and after-colon strings respectively in `setName` and `tabName`; if no colon is detected, `splitSetTabName()` issues a warning (if `noColonFound` is not given), returns the entire string in `setName`, and also attempts to extract the name of the first table in the dataset (unless `useBlock` is given and is .false.) and returns this in `tabName`, which can be an empty string. In the latter case, if the file does not exist and if `noColonFound` is not given, then it raises an error.

An example of how to use `splitSetTabName()` is as follows:



```
setTabName = stringParameter('mytable') ! this should be of param type 'table'  
call splitSetTabName(setTabName, setName, tabName)  
set = dataSet(setName, READ)  
tab = table(set, tabName)  
  
...
```

7.2 readArrayData

It is often useful to be able to read an array of any data type into a fortran array of a single data type. The following interface covers just about every combination I could think of.

```
interface readArrayData  
    subroutine readArrayDataName1dReal32(imageSetName, vector)  
        character(*), intent(in) :: imageSetName  
        real(single), pointer :: vector(:)  
    end subroutine readArrayDataName1dReal32  
  
    subroutine readArrayDataName2dReal32(imageSetName, image)  
        character(*), intent(in) :: imageSetName  
        real(single), pointer :: image(:, :)  
    end subroutine readArrayDataName2dReal32  
  
    subroutine readArrayDataName3dReal32(imageSetName, cube)  
        character(*), intent(in) :: imageSetName  
        real(single), pointer :: cube(:, :, :)  
    end subroutine readArrayDataName3dReal32  
  
    subroutine readArrayDataName1dReal64(imageSetName, vector)  
        character(*), intent(in) :: imageSetName  
        real(double), pointer :: vector(:)  
    end subroutine readArrayDataName1dReal64  
  
    subroutine readArrayDataName2dReal64(imageSetName, image)  
        character(*), intent(in) :: imageSetName  
        real(double), pointer :: image(:, :)  
    end subroutine readArrayDataName2dReal64  
  
    subroutine readArrayDataName3dReal64(imageSetName, cube)  
        character(*), intent(in) :: imageSetName  
        real(double), pointer :: cube(:, :, :)  
    end subroutine readArrayDataName3dReal64  
  
    subroutine readArrayDataName2dBool(imageSetName, image)  
        character(*), intent(in) :: imageSetName  
        logical(bool), pointer :: image(:, :)  
    end subroutine readArrayDataName2dBool  
  
    subroutine readArrayDataName2dInt16(imageSetName, image)  
        character(*), intent(in) :: imageSetName  
        integer(int16), pointer :: image(:, :)  
    end subroutine readArrayDataName2dInt16
```



```
subroutine readArrayDataName2dInt32(imageSetName, image)
    character(*), intent(in) :: imageSetName
    integer(int32), pointer :: image(:, :)
end subroutine readArrayDataName2dInt32

subroutine readArrayDataArray1dReal32(inArray, vector)
    type(ArrayT), intent(in) :: inArray
    real(single), pointer :: vector(:)
end subroutine readArrayDataArray1dReal32

subroutine readArrayDataArray2dReal32(inArray, image)
    type(ArrayT), intent(in) :: inArray
    real(single), pointer :: image(:, :)
end subroutine readArrayDataArray2dReal32

subroutine readArrayDataArray3dReal32(inArray, cube)
    type(ArrayT), intent(in) :: inArray
    real(single), pointer :: cube(:, :, :)
end subroutine readArrayDataArray3dReal32

subroutine readArrayDataArray1dReal64(inArray, vector)
    type(ArrayT), intent(in) :: inArray
    real(double), pointer :: vector(:)
end subroutine readArrayDataArray1dReal64

subroutine readArrayDataArray2dReal64(inArray, image)
    type(ArrayT), intent(in) :: inArray
    real(double), dimension(:, :, ), pointer :: image
end subroutine readArrayDataArray2dReal64


subroutine readArrayDataArray3dReal64(inArray, cube)
    type(ArrayT), intent(in) :: inArray
    real(double), dimension(:, :, :, ), pointer :: cube
end subroutine readArrayDataArray3dReal64

subroutine readArrayDataArray2dBool(inArray, image)
    type(ArrayT), intent(in) :: inArray
    logical(bool), dimension(:, :, ), pointer :: image
end subroutine readArrayDataArray2dBool

subroutine readArrayDataArray2dInt16(inArray, image)
    type(ArrayT), intent(in) :: inArray
    integer(int16), dimension(:, :, ), pointer :: image
end subroutine readArrayDataArray2dInt16

subroutine readArrayDataArray2dInt32(inArray, image)
    type(ArrayT), intent(in) :: inArray
    integer(int32), dimension(:, :, ), pointer :: image
end subroutine readArrayDataArray2dInt32
end interface
```

Boolean values are converted to real or integer 0s and 1s; real or integer are converted to boolean TRUE if ≥ 0 , FALSE otherwise.



Where the dimensions of the dataset array don't match those of the to-be-returned pointer array, it is eventually intended to convert these as follows:

Dims:	Out 1	Out2	Out 3
In 1	simple	-i:image(1,:)	-i:cube(1,1,:)
In 2	take 1st row	simple	-i:cube(1,:,:)
In 3	take 1st row, 1st plane	take 1st plane	simple
In i3	not supported	not supported	not supported

First rows or planes are always aligned with the biggest dimension(s).

However most of the inter-dimensional functionality is not yet in place.

Note that the returned pointer is not associated with any pointer allocated by a **dal** call such as, for example:

```
arrayDataReal32 => real32Array2Data(inArray)
```

Where readArrayData is called with the name of image dataset, the dataset is released within the subroutine, and all such dataset pointers are at that time deallocated; if readArrayData is called instead with the pointer inArray specified, the dataset and its array remain open, all dataset pointers which were allocated within the subroutine also remain allocated, but deallocate in the normal way at the time the calling routine releases the dataset (or its array). In either case, the returned pointer argument 'vector', 'image', or 'cube' REMAINS ALLOCATED and therefore should be expressly deallocated in the calling routine via the fortran 'deallocate' statement.

7.3 addOrOpenColumn

```
function addOrOpenColumn(tab, colName, dataType, units, comment)&
result(col)
    type(TableT), intent(in) :: tab
    character(*), intent(in) :: colName
    integer(int32), intent(in), optional :: dataType
    character(*), intent(in), optional :: units, comment
    type(ColumnT) :: col
end function addOrOpenColumn
```

This function opens the column if hasColumn(tab, colName) returns TRUE but adds a new column of this name if not. If a new column is created, defaults for the optional arguments 'dataType', 'units' and 'comment' are REAL32, " and " respectively.

7.4 readColDataToFixed

This is similar in intention to readArrayData (subsection 7.2). The interface below covers most combinations.

```
interface readColDataToFixed
    subroutine readColToFixedNameReal32(tab, colName, colData)
        type(TableT), intent(in) :: tab
```



```
character(*), intent(in) :: colName
  real(single), intent(out) :: colData(:)
end subroutine readColToFixedNameReal32

subroutine readColToFixedNameReal64(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  real(double), intent(out) :: colData(:)
end subroutine readColToFixedNameReal64

subroutine readColToFixedNameInt8(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int8), intent(out) :: colData(:)
end subroutine readColToFixedNameInt8

subroutine readColToFixedNameInt16(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int16), intent(out) :: colData(:)
end subroutine readColToFixedNameInt16

subroutine readColToFixedNameInt32(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int32), intent(out) :: colData(:)
end subroutine readColToFixedNameInt32

subroutine readColToFixedNameStr(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  character(*), intent(out) :: colData(:)
end subroutine readColToFixedNameStr

subroutine readColToFixedNameBool(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  logical(bool), intent(out) :: colData(:)
end subroutine readColToFixedNameBool

subroutine readColToFixedCol2dReal32(col, colData)
  type(ColumnT), intent(in) :: col
  real(single), intent(out) :: colData(:, :)
end subroutine readColToFixedCol2dReal32

subroutine readColToFixedCol2dReal64(col, colData)
  type(ColumnT), intent(in) :: col
  real(double), intent(out) :: colData(:, :)
end subroutine readColToFixedCol2dReal64

subroutine readColToFixedColReal32(col, colData)
  type(ColumnT), intent(in) :: col
  real(single), intent(out) :: colData(:)
end subroutine readColToFixedColReal32
```



```
subroutine readColToFixedColReal64(col, colData)
  type(ColumnT), intent(in) :: col
  real(double), intent(out) :: colData(:)
end subroutine readColToFixedColReal64

subroutine readColToFixedColInt8(col, colData)
  type(ColumnT), intent(in) :: col
  integer(int8), intent(out) :: colData(:)
end subroutine readColToFixedColInt8

subroutine readColToFixedColInt16(col, colData)
  type(ColumnT), intent(in) :: col
  integer(int16), intent(out) :: colData(:)
end subroutine readColToFixedColInt16

subroutine readColToFixedColInt32(col, colData)
  type(ColumnT), intent(in) :: col
  integer(int32), intent(out) :: colData(:)
end subroutine readColToFixedColInt32

subroutine readColToFixedColStr(col, colData)
  type(ColumnT), intent(in) :: col
  character(*), intent(out) :: colData(:)
end subroutine readColToFixedColStr

subroutine readColToFixedColBool(col, colData)
  type(ColumnT), intent(in) :: col
  logical(bool), intent(out) :: colData(:)
end subroutine readColToFixedColBool
end interface
```


The rules for conversion between datatypes are the same as for readArrayData (subsection 7.2). There is at present no conversion between non-string data and a string-valued ‘colData’ argument.

Note that the argument ‘colData’ is NOT a pointer and thus should be made the same size as the column to be read in the calling program.

7.5 readColDataToPtr

These are exactly the same as those routines described in subsection 7.4, except that now the argument ‘colData’ is a pointer array. This allows the calling routine to avoid having to size it before the call to readColDataToPtr, on the other hand ‘colData’ should now be DEALLOCATED by the calling program after use. As with readArrayData (subsection 7.2), there is no association between ‘colData’ and the dataset pointers opened within the subroutine, which are either disassociated within the subroutine (if readColDataToPtr was called with the column name) or at the time the calling program releases the dataset (if readColDataToPtr was called with the column pointer).

```
interface readColDataToPtr
  subroutine readColToPtrName2dReal32(tab, colName, colData)
    type(TableT), intent(in) :: tab
    character(*), intent(in) :: colName
    real(single), pointer :: colData(:, :)
```



```
end subroutine readColToPtrName2dReal32

subroutine readColToPtrName2dReal64(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  real(double), pointer    :: colData(:, :)
end subroutine readColToPtrName2dReal64

subroutine readColToPtrNameReal32(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  real(single), pointer   :: colData(:)
end subroutine readColToPtrNameReal32

subroutine readColToPtrNameReal64(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  real(double), pointer   :: colData(:)
end subroutine readColToPtrNameReal64

subroutine readColToPtrNameInt8(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int8), pointer  :: colData(:)
end subroutine readColToPtrNameInt8

subroutine readColToPtrNameInt16(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int16), pointer :: colData(:)
end subroutine readColToPtrNameInt16

subroutine readColToPtrNameInt32(tab, colName, colData)
  type(TableT), intent(in) :: tab
  character(*), intent(in) :: colName
  integer(int32), pointer :: colData(:)
end subroutine readColToPtrNameInt32

subroutine readColToPtrColReal32(col, colData)
  type(ColumnT), intent(in) :: col
  real(single), pointer    :: colData(:)
end subroutine readColToPtrColReal32

subroutine readColToPtrColReal64(col, colData)
  type(ColumnT), intent(in) :: col
  real(double), pointer    :: colData(:)
end subroutine readColToPtrColReal64

subroutine readColToPtrColInt8(col, colData)
  type(ColumnT), intent(in) :: col
  integer(int8), pointer   :: colData(:)
end subroutine readColToPtrColInt8

subroutine readColToPtrColInt16(col, colData)
  type(ColumnT), intent(in) :: col

```



```
    integer(int16), pointer      :: colData(:)
end subroutine readColToPtrColInt16

subroutine readColToPtrColInt32(col, colData)
  type(ColumnT), intent(in) :: col
  integer(int32), pointer   :: colData(:)
end subroutine readColToPtrColInt32
end interface
```

The rules for conversion between datatypes are the same as for readArrayData (subsection 7.2). There is at present no conversion between non-string data and a string-valued ‘colData’ argument.

7.6 minNonNullValue

This and the following subroutine are useful if you want to find min and max values of a column (at present restricted to REAL32 and REAL64 data types) but have reason to fear that nulls may be present. Real-valued nulls can do funny things to fortran minval() and maxval() functions.


```
interface minNonNullValue
  subroutine minNonNullValueSingle(tab, colName, minValue, allRowsNull)
    type(TableT), intent(in)  :: tab
    character(*), intent(in)  :: colName
    real(single), intent(out) :: minValue
    logical(bool), intent(out) :: allRowsNull
  end subroutine minNonNullValueSingle

  subroutine minNonNullValueDouble(tab, colName, minValue, allRowsNull)
    type(TableT), intent(in)  :: tab
    character(*), intent(in)  :: colName
    real(double), intent(out) :: minValue
    logical(bool), intent(out) :: allRowsNull
  end subroutine minNonNullValueDouble
end interface
```

7.7 maxNonNullValue

```
interface maxNonNullValue
  subroutine maxNonNullValueSingle(tab, colName, maxValue, allRowsNull)
    type(TableT), intent(in)  :: tab
    character(*), intent(in)  :: colName
    real(single), intent(out) :: maxValue
    logical(bool), intent(out) :: allRowsNull
  end subroutine maxNonNullValueSingle

  subroutine maxNonNullValueDouble(tab, colName, maxValue, allRowsNull)
    type(TableT), intent(in)  :: tab
    character(*), intent(in)  :: colName
    real(double), intent(out) :: maxValue
    logical(bool), intent(out) :: allRowsNull
  end subroutine maxNonNullValueDouble
end interface
```



7.8 getDataType

This function returns the dataType (see **dal**) of a given FITS-image or table-column. For the input FITS filename, the form of ‘ABC.fits:TABNAME’ is allowed, where the TABNAME is the name of the FITS extention of interest. The priority order for the table-name (tabName) in given setTabName, extention number (extNum) and extention name (extName) explicitly given is

extName > tabName > extNum,

that is, extName is always considered first if given. Note that if the given extName (or tabName) is an empty string, it is ignored and the next highest priority one is used.

```
interface dataType
    function dataTypeFromName(setTabName, extNum, extName, colName) result(iType)
        integer :: iType
        character(*), intent(in) :: setTabName
        integer, intent(in), optional :: extNum
        character(*), intent(in), optional :: extName, colName
    end function dataTypeFromName


    function dataTypeFromSet(set, extNum, extName, colName) result(iType)
        integer :: iType
        type(DataSetT), intent(in) :: set
        integer, intent(in), optional :: extNum
        character(*), intent(in), optional :: extName, colName
    end function dataTypeFromSet

    function dataTypeFromTab(tab, colName) result(iType)
        integer :: iType
        type(TableT), intent(in) :: tab
        character(*), intent(in) :: colName
    end function dataTypeFromTab
end interface
```

7.9 getTypeName

This function returns the string expression for the given Integer as the datatype. This is meant to be used (mainly) in debugging. See `/packages/dal/interface/dal.f90` for detail re the definition.

```
interface getTypeName
    subroutine getTypeName(inInt, outStr)
        integer, intent(in) :: inInt
        character(*), intent(out) :: outStr
    end subroutine getTypeName
end interface
```



7.10 getAttributeTypeName

This function returns the string expression for the given Integer as the data-attribute-type. This is meant to be used (mainly) in debugging. See /packages/dal/interface/dal.f90 for detail re the definition.

```
interface getAttributeTypeName
  subroutine getAttributeTypeName(inInt, outStr)
    integer, intent(in) :: inInt
    character(*), intent(out) :: outStr
  end subroutine getAttributeTypeName
end interface
```

8 Poissonian statistics and source detectability in this regime

Module name: `detection_stats`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

The subroutines in this module deal broadly with source detection in the Poissonian regime.

8.1 Integrated χ^2 probability

This subroutine gives the probability $P_\chi(\chi^2; \nu)$ of exceeding chi^2 for a given number of degrees of freedom ν , i.e., the single-sided integrated probability, where $P_x(x^2; \nu)$ is the χ^2 probability distribution function (e.g., see Appendix C.4 in Bevington & Robinson (1992, “Data reduction and error analysis for the physical sciences”, 2nd edition)).

```
subroutine integratedChi2Prob(chi2, degFree, probability, status)
  real(single), intent(in)          :: chi2
  integer,      intent(in)          :: degFree ! or real(single)
  real(single), intent(out)         :: probability
  integer,      intent(out), optional :: status
end subroutine integratedChi2Prob
```

The optional argument `status` is returned as follows;

Status	Description
$n(n > 0)$	(status in <code>incompleteGammaQ</code> ; see <code>math_utils</code> , Section 1)
0	Normal end
-1	When the given $\text{chi}^2 \leq 0$
-2	When the given $\text{degFree} \leq 0$
$n(n < -2)$	((status in <code>incompleteGammaQ</code>) -2; see <code>math_utils</code> , Sect

8.2 Poisson probability

This returns the probability $P(i)$ of the occurrence of an integer i according to the Poisson distribution

$$P(i) = \frac{a^i \exp(-a)}{i!}$$



where a is the average or expectation value of i .

Note that the argument may also be a real number. In this case what is returned is

$$p(r) = \frac{a^r \exp(-a)}{\Gamma(r+1)}$$

The value p is not quite a probability density: it would need to be normalized by

$$\int_0^{\infty} dr \frac{a^r \exp(-a)}{\Gamma(r+1)}$$

in order for this to be true. However it does have the property that, if $r = i$, $p(r) = P(i)$.

```
interface poissonProb
    real function poissonProbSingle(av, realI)
        real(single), intent(in) :: av, realI
    end function poissonProbSingle

    real function poissonProbInt32(av, i)
        real(single), intent(in) :: av
        integer(int32), intent(in) :: i
    end function poissonProbInt32
end interface
```

8.3 Integrated Poisson probability

This function returns the probability that an integer random variable which obeys a Poisson distribution about an average ‘av’ will EQUAL OR EXCEED ‘i’.


```
real(single) function integratedPoissonProb(av, i)
    real(single), intent(in) :: av
    integer, intent(in) :: i
end function integratedPoissonProb
```

8.4 Source detection limits

The logic of source detection goes as follows. Let us assume to begin with that there is no source at a given location, only background. Let us calculate the probability that the observed counts at that location are due solely to background. If this probability is less than a specified value, our initial assumption was incorrect and there is in fact a source at that location.

The routines described in the present section are designed to take as arguments the probability cutoff (actually a cutoff in likelihood is used) and the background, or expectation value for the counts, and use them to calculate the minimum value of source counts which is detectable at those levels.

To elaborate: given a discrete probability distribution $p(j)$ of event counts j , any sample value c is associated with a certain probability p_{int} (and therefore likelihood $L = -\ln(p_{\text{int}})$) of it *not* being due to



chance. This probability is obtained by summing the probability values $p(j)$ from $j = c$ to $j = \inf$. For p given by the Poisson distribution, this sum is equal to the incomplete gamma function $P(c, a)$, where a is the expectation value of c . In mathematical terms, the Poissonian likelihood is thus

$$L = -\ln[P(c, a)]. \quad (1)$$

(Note: This is ONLY true if the uncertainty in the background or expectation value is insignificant.) The two subroutines described in the present section invert equation 1 to return that value of c which is associated with specified L and a .

8.4.1 Single-band detection

```
interface minDetPoissonCounts
  subroutine minDetPoissonCountsScalar(bkgCount, likelihoodCutoff&
, detectableSrcCount, detectableSrcCountUncert, status)
    real(single), intent(in)           :: bkgCount, likelihoodCutoff
    real(single), intent(out)          :: detectableSrcCount
    real(single), intent(out)          :: detectableSrcCountUncert
    integer,      intent(out), optional :: status
  end subroutine minDetPoissonCountsScalar
```

8.4.2 Parallel detection over N bands (with no assumptions made about source spectrum)

Here the situation is a little more complicated. If nothing can be assumed about the spectra of the sources, the best detection strategy appears to be as follows:


- Detect in each band separately.
- Calculate likelihood values according to equation 1.
- Add the band likelihoods together for each position.

This sum over likelihoods itself follows a Poisson-like distribution. It can thus be shown that the overall likelihood for any given value of this sum being not due to chance, ie, the overall likelihood L_{total} that there is a source at this position, is given by

$$L_{\text{total}} = -\ln\left\{1 - P\left[f(N), \sum_{i=1}^N L_i\right]\right\}.$$

where $f(x)$ approximates a linear function of x of slope 1. Monte Carlo studies indicate that $f(2) \sim 2$, $f(5) \sim 4$, $f(10) \sim 8$ and so forth; however **eboxdetect** at the present time assumes that $f(N) = N$; hence that (arguably not quite correct) assumption has been built into the present subroutine as well.

```
subroutine minDetPoissonCountsVector(bkgCounts, likelihoodCutoff&
, detectableSrcCounts, detectableSrcCountsUncert, srcCountRatios, status)
```



```
real(single), intent(in)          :: srcCountRatios(:),&
                                    bkgCounts(size(srcCountRatios)),&
                                    likelihoodCutoff
real(single), intent(out)         :: detectableSrcCounts(&
                                    size(srcCountRatios))
real(single), intent(out)         :: detectableSrcCountsUncert(&
                                    size(srcCountRatios))
integer,      intent(out), optional :: status
end subroutine minDetPoissonCountsVector
end interface minDetPoissonCounts
```

8.5 Integrated Gaussian probability

This function returns the probability that a gaussian-distributed variable y will depart from the mean y_{mean} by greater than $\text{abs}(y - y_{\text{mean}})$. For values obeying a gaussian distribution of standard deviation σ , the probability P of a given y value (or greater) occurring by chance is

$$P(y) = 1 - \text{erf}[\text{abs}(y - y_{\text{mean}})/\sigma\sqrt{2}].$$

```
function integratedGaussProb(testY, meanY, sigma) result(probability)
  real(single), intent(in) :: testY, meanY, sigma
  real(single) :: probability
end function integratedGaussProb
```

8.6 ‘Degrees of freedom’ for a sum of likelihoods

```
function calcChi2HalfDegFree(numLikelihoods) result(f)
  integer(int16), intent(in) :: numLikelihoods
  real(single)           :: f
end function calcChi2HalfDegFree
```

A sum over likelihoods seems to have a probability distribution similar to that of a χ^2 distribution with $2f$ degrees of freedom. The factor f is approximately equal to the number of likelihoods in the sum but not quite. However for the time being (until more accurate information is available, that is) it is assumed that the equality holds exactly.


9 DSS utilities

Module name: `dss_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

The routines are designed to act as an additional layer over the `dsslib` library. They implement many useful short cuts.

Full information about the Data Sub Space (DSS) should of course be sought in the `dsslib` task documentation. However a few explanatory words here would not be out of place.



The function of the DSS is to store information about the criteria used to select events. Thus an XMM event list may contain a DSS if it has been filtered in some way; XMM products such as light curves or spectra, which have been created from event lists, nearly always filtered, may also contain them.

The formal structure of a DSS comprises a list of components, each of which may contain a list of filters. Supposedly the selection should be reconstructed by ANDing all the filters for each component then ORing all the components, but many filter types (eg GTIs) imply a logical OR internal to the filter.

The DSS is implemented in terms of keywords and extensions, but it is not intended that the user should need to know how the DSS is encoded in these things: the **dsslib** library supplies subroutines to permit basic access to the DSS details without this knowledge.

9.1 Routines which involve the whole DSS

9.1.1 hasDss

Tests whether a dataset, array or table has a Data Sub Space (DSS) attached.

```
logical(bool) function hasDssSet(set)
    type(DataSetT), intent(in) :: set
end function hasDssSet

logical(bool) function hasDssArray(inArray)
    type(ArrayT), intent(in) :: inArray
end function hasDssArray

logical(bool) function hasDssTab(tab)
    type(TableT), intent(in) :: tab
end function hasDssTab

logical(bool) function hasDssBlock(inBlock)
    type(BlockT), intent(in) :: inBlock
end function hasDssBlock
```


9.1.2 dumpDss

Dumps contents of a DSS to STDOUT.

```
subroutine dumpDssBlock(inBlock)
    type(BlockT), intent(in) :: inBlock
end subroutine dumpDssBlock

subroutine dumpDssPointer(dssPointer)
    type(DssT), intent(in) :: dssPointer
end subroutine dumpDssPointer

subroutine dumpDssComponent(dssComp)
    type(DScompT), intent(in) :: dssComp
end subroutine dumpDssComponent
```



9.2 Routines which return information about DSS components

Each DSS component contains several filters. Each filter is associated with the name of the event-list column (called in DSS-speak the 'axis' name) which was filtered (for some filter types, eg REGIONFILTERT, two names are supplied), plus a specification for a set of values of that (or those) column(s).

9.2.1 getNum1stDssCompWithValue

Returns the number of the first component which has a filter of the specified column or 'axis' name which passes the specified value. This searches only filters on single columns.

Note that the component number is meaningful for several **dsslib** calls, eg dssComponent(). Component numbers start from zero.

```
subroutine getNum1stDssCompWithValue(dssPointer, axisName, axisValue&
, firstCompNum)
  type(DssT), intent(in) :: dssPointer
  character(*), intent(in) :: axisName
  real(single), intent(in) :: axisValue
  integer, intent(out) :: firstCompNum
end subroutine getNum1stDssCompWithValue
```

9.2.2 numDssCompsOfAxis

Returns the number of components which have at least 1 filter on the specified axis. (Note that this searches only filters on single columns.)

```
integer function numDssCompsOfAxis(dssPointer, axisName)
  type(DssT), intent(in) :: dssPointer
  character(*), intent(in) :: axisName
end function numDssCompsOfAxis
```

9.2.3 numDssCompsWithValue

Returns the number of components which have a filter of the specified column or 'axis' name which passes the specified value. This searches only filters on single columns.

```
integer function numDssCompsWithValue(dssPointer, axisName, axisValue)
  type(DssT), intent(in) :: dssPointer
  character(*), intent(in) :: axisName
  real(single), intent(in) :: axisValue
end function numDssCompsWithValue
```



9.3 Routines which return information about the filters in a specific component

9.3.1 valueIsPassedByDssComp

Returns TRUE if the component has a filter of the specified column or 'axis' name which passes the specified value. This searches only filters on single columns.

```
logical(bool) function valueIsPassedByDssComp(dssComp, axisName, axisValue)
  type(DScompT), intent(in) :: dssComp
  character(*), intent(in) :: axisName
  real(single), intent(in) :: axisValue
end function valueIsPassedByDssComp
```

9.3.2 anyFilterOfThisAxis

Returns TRUE if the component has a filter of the specified column or 'axis' name. This searches only filters on single columns.

```
logical(bool) function anyFilterOfThisAxis(dssComp, axisName)
  type(DScompT), intent(in) :: dssComp
  character(*), intent(in) :: axisName
end function anyFilterOfThisAxis
```

9.3.3 numFiltersOfAxis

Returns the number of filters on the specified column or 'axis' name. This searches only filters on single columns.

```
integer function numFiltersOfAxis(dssComp, axisName)
  type(DScompT), intent(in) :: dssComp
  character(*), intent(in) :: axisName
end function numFiltersOfAxis
```

9.3.4 get1stFilterThisAxis

Returns the handle of the first filter on the specified column or 'axis' name. This searches only filters on single columns.

```
subroutine get1stFilterThisAxis(dssComp, axisName, firstFilter, status)
  type(DScompT), intent(in) :: dssComp
  character(*), intent(in) :: axisName
  type(DSfilterT), intent(out) :: firstFilter
  integer, intent(out) :: status
end subroutine get1stFilterThisAxis
```



9.3.5 allFiltersPassValue

Returns TRUE if all filters of the specified axis name in the specified component pass the specified value.

```
logical(bool) function allFiltersPassValue(dssComp, axisName, axisValue)
  type(DScompT), intent(in) :: dssComp
  character(*), intent(in) :: axisName
  real(single), intent(in) :: axisValue
end function allFiltersPassValue
```

9.3.6 valueIsPassedByFilter

Returns TRUE if the specified filter passes the value.

```
logical(bool) function valueIsPassedByFilter(value, filter)
  real(single), intent(in) :: value
  type(DSfilterT), intent(in) :: filter
end function valueIsPassedByFilter
```

9.4 Routines which act on DSS RangeT scalars

The DSS structure type RangeT is described in **dsslib**. It specifies a lower and an upper bound to an interval on the real line, and the types of these bounds. Possible types are INCLUSIVE (which means the bound is included in the interval), EXCLUSIVE (which means the bound is not included in the interval) and UNDEFINED in which case there is no bound at this end of the interval.

Note that the integer constants INCLUSIVE, EXCLUSIVE and UNDEFINED are defined in **dsslib**.

9.4.1 copyRange


Copies one range structure to another.

```
function copyRange(inRange) result(outRange)
  type(RangeT), intent(in) :: inRange
  type(RangeT) :: outRange
end function copyRange
```

9.4.2 checkRangeOverlap

This function compares two ranges to see if they overlap, and if not, which is higher than the other. An integer value is returned, which has the possible values BOVERLAPSA, BISTOOHIGH, BISTOOLOW. These integer constants are defined in the present module.

```
function checkRangeOverlap(rangeA, rangeB) result(status)
  type(RangeT), intent(in) :: rangeA, rangeB
```



```
    integer :: status
end function checkRangeOverlap
```

9.4.3 andRangePair

This subroutine takes two overlapping ranges and returns a single range which contains the region of overlap.

Note that the function will not work UNLESS THE RANGES OVERLAP as tested by checkRangeOverlap() (see section 9.4.2).

```
function andRangePair(rangeA, rangeB) result(andedRanges)
  type(RangeT), intent(in) :: rangeA, rangeB
  type(RangeT)           :: andedRanges
end function andRangePair
```

9.4.4 orRangePair

This subroutine takes two overlapping ranges and returns a single range which contains the sum of the two ranges.

Note that the function will not work UNLESS THE RANGES OVERLAP as tested by checkRangeOverlap() (see section 9.4.2).

```
function orRangePair(rangeA, rangeB) result(oredRanges)
  type(RangeT), intent(in) :: rangeA, rangeB
  type(RangeT)           :: oredRanges
end function orRangePair
```

9.4.5 valueIsWithinRange


Returns TRUE if the value is within the specified range.

```
logical(bool) function valueIsWithinRangeSingle(value, range)
  real(single), intent(in) :: value
  type(RangeT), intent(in) :: range
end function valueIsWithinRangeSingle

logical(bool) function valueIsWithinRangeInt32(value, range)
  integer(int32), intent(in) :: value
  type(RangeT), intent(in) :: range
end function valueIsWithinRangeInt32
```

9.5 Routines which act on DSS RangeT vectors

See section 9.4 for some additional information about the **dsslib** RangeT structure type.



The routines in the present section deal with vectors of ranges.

9.5.1 rangesAreWellFormed

A RangeT vector (of size N) is defined as well-formed if and only if it obeys the following conditions:

- Only the lowest and highest bounds of the sequence of ranges are permitted to be of type UNDEFINED.
- For each range for which neither the lower or upper bound is of type UNDEFINED (ie, for each internal range in the sequence), the upper bound value must exceed the lower bound value unless both both bound types are INCLUSIVE, in which case the upper bound value may equal the lower bound value. In other words, each range must encompass some non-empty set of real numbers.
- For all i from 1 to N-1, the upper bound of range i must be less than the lower bound of range i+1, unless both bounds are of type EXCLUSIVE, in which case the upper bound of range i may equal the lower bound of range i+1. In other words, the gap between two adjacent ranges must encompass some non-empty set of real numbers.

Note that any ranges pointer can be brought into valid condition by passing it through the subroutine correctRanges() (section 9.5.4).

```
logical(bool) function rangesAreWellFormed(ranges)
    type(RangeT), intent(in) :: ranges(:)
end function rangesAreWellFormed
```

9.5.2 copyRanges

Copies one vector of ranges to another.

NOTE! You should deallocate the pointer outRanges() after use.


```
subroutine copyRanges(inRanges, outRanges)
    type(RangeT), intent(in) :: inRanges(:)
    type(RangeT), pointer     :: outRanges(:)
end subroutine copyRanges
```

9.5.3 readRanges

The function of this subroutine is to return a vector containing all the ranges from all filters on the axis ‘axisName’.

NOTE! The returned pointer ranges() should be deallocated after use.

```
% subroutine readRangesDss(dssPointer, axisName, ranges, dssConstraints)
% subroutine readRangesDss(dssPointer, axisName, ranges)
```



```
type(DssT), intent(in) :: dssPointer
character(*), intent(in) :: axisName
type(RangeT), pointer :: ranges(:)
% type(dssConstraintType), intent(in), optional :: dssConstraints(:)
end subroutine readRangesDss

subroutine readRangesComp(dssComp, axisName, ranges)
type(DScompT), intent(in) :: dssComp
character(*), intent(in) :: axisName
type(RangeT), pointer :: ranges(:)
end subroutine readRangesComp
```

9.5.4 correctRanges

This takes a vector of ranges and returns them in a well-formed sequence (see section 9.5.1). Note that the argument is a pointer because the operation may change the number of elements.

```
subroutine correctRanges(ranges)
type(RangeT), pointer :: ranges(:)
end subroutine correctRanges
```

9.5.5 integrateRanges

This is a function to perform numerical integration of $y(x)$ (using the trapezoid rule) over a set of discrete ranges specified via the $xRanges$ argument.

NOTE! (i) The values in the vector $x()$ should be in increasing order. (ii) The ranges may occur in any order, but are otherwise assumed to be well-formed. (iii) If any upper range bound is undefined, the upper x value is used instead for that range bound; likewise for undefined lower bounds.

!*** should change it so that the ranges are required to be well-formed. This would make the routine less general but makes the accepted properties of ranges simpler.

```
interface integrateRanges
function integrateRangesScalar(x, y, xRange) result(approxIntegral)
real(single), intent(in) :: x(:, y(size(x)))
type(RangeT), intent(in) :: xRange
real(single) :: approxIntegral
end function integrateRangesScalar

function integrateRangesVector(x, y, xRanges) result(approxIntegral)
real(single), intent(in) :: x(:, y(size(x)))
type(RangeT), intent(in) :: xRanges(:)
real(single) :: approxIntegral
end function integrateRangesVector
end interface
```



9.5.6 andRangesPair

This function takes as input two sequences of ranges and returns a sequence which contains all overlaps between the input ranges.

Points to note:

- The input range sequences must be well-formed (see section 9.5.1). The output is well-formed.
- The function returns a pointer argument. Deallocating this correctly is a little tricky, and I may eventually turn this (and all similar functions) into a subroutine. The function should NOT be called iteratively as in the following example:

```
andedRanges => andRangesPair(andedRanges, rangesB)
```

The memory that the pointer andedRanges pointed to before the call now has no pointer to it, since at the moment the call is executed andedRanges is reassigned to the same memory that the function points to, which was newly assigned during the call. The initial memory pointed to by andedRanges therefore cannot now be deallocated. Better would be:

```
tempAndedRanges => andRangesPair(andedRanges, rangesB)
deallocate(andedRanges)
andedRanges => tempAndedRanges
```

Then later, when appropriate, deallocate(andedRanges) for the final time.

```
% function andRangesPair(rangesA, rangesB, doChecks) result(andedRanges)
function andRangesPair(rangesA, rangesB) result(andedRanges)
    type(RangeT), intent(in) :: rangesA(:), rangesB(:)
    type(RangeT), pointer     :: andedRanges(:)
%    logical(bool), intent(in), optional :: doChecks
end function andRangesPair
```

9.5.7 orRangesPair

This function takes as input two sequences of ranges and returns a sequence which contains the sum of the input ranges. The returned sequence of ranges is well-formed but, in contrast to the function andRangesPair(), the inputs are not required to be well-formed. NOTE however that the same considerations re pointer deallocation also apply here.

```
function orRangesPair(rangesA, rangesB) result(oredRanges)
    type(RangeT), intent(in) :: rangesA(:), rangesB(:)
    type(RangeT), pointer     :: oredRanges(:)
end function orRangesPair
```

9.5.8 dumpRanges

Prints the ranges to standard output.



```
subroutine dumpRanges(ranges)
    type(RangeT), intent(in) :: ranges(:)
end subroutine dumpRanges
```

***** andIntervals

9.6 Routines which deal with DSS GTI filters

GTIs are contained in structures of type IntervalT, which is defined in the module caltypes. This is similar to RangeT except that no type is given for the upper and lower bounds. Where I have translated GTIs into ranges (see for example section 9.6.3) I have taken the lower GTI bound to be INCLUSIVE and the upper to be EXCLUSIVE. A well-formed sequence of GTIs (of size N) should therefore obey the following criteria:

- For each GTI in the sequence, the upper bound value must exceed the lower bound value.
- For all i from 1 to N-1, the upper bound of GTI i must be less than the lower bound of GTI i+1.

There are currently no routines to test or correct the format of non-well-formed sequences of GTIs.

See also section 16.

9.6.1 readGtis

This subroutine extracts from the DSS the sequence of GTIs used to filter events on a specified CCD chip. (The routine assumes that all events which occur on a given CCD chip share a common GTI selection.)

The pointer gti() should be deallocated after use.

```
subroutine readGtis(set, inBlock, ccdNum, gti)
    type(DataSetT), intent(in) :: set
    type(BlockT),   intent(in) :: inBlock
    integer,         intent(in) :: ccdNum
    type(IntervalT), pointer    :: gti(:)
end subroutine readGtis
```

9.6.2 getGtiFromFilter

This subroutine extracts a GTI sequence from a single DSS filter.

The pointer gti() should be deallocated after use.

```
subroutine getGtiFromFilter(set, filter, gti)
    type(DataSetT), intent(in) :: set
    type(DSfilterT), intent(in) :: filter
    type(IntervalT), pointer    :: gti(:)
end subroutine getGtiFromFilter
```



9.6.3 andGtis

This function takes as input two sequences of GTIs and returns a sequence which contains all overlaps between the input GTIs. The function makes use of the function andRangesPair() (see section 9.5.6) and similar considerations apply.

```
function andGtis(gtia, gtib) result(andedGti)
  type(IntervalT), intent(in) :: gtia(:), gtib(:)
  type(IntervalT), pointer    :: andedGti(:)
end function andGtis
```

9.7 Routines which deal with DSS bitmask filters

The format of DSS bit masks is a bit more complicated than it used to be. Basically a bit mask is an integer (in SAS usage usually 32 bits in size), each bit of which is intended to be interpreted in a boolean sense. However the **dsslib** call dssFilterMask() now returns two pointers, onBitMasks and offBitMasks, each of which contains a sequence of masks.

The pointers onBitMasks and offBitMasks are supposed to always be the same size, although there is nothing at the API level to force this to be the case. This is a little unfortunate perhaps and to correct this I have defined in the present module a structure BitMaskT which contains an 'on' mask and an 'off' mask.

9.7.1 getBitMasksFromFilter

This subroutine acts as a wrapper around the **dsslib** routine dssFilterMask(). It retrieves the on and off bit masks from the specified DSS filter, checks that they are the same size, and returns them in a pointer bitMaskPtr of type BitMaskT.

```
subroutine getBitMasksFromFilter(filter, bitMaskPtr)
  type(DSfilterT), intent(in) :: filter
  type(BitMaskT), pointer    :: bitMaskPtr(:)
end subroutine getBitMasksFromFilter
```

9.7.2 allBitsEquiv

This function tests all the values of the specified bit in the on-masks for logical equivalence and all the values in the off-masks for equivalence and returns TRUE if the equivalence holds. Note that bitNum starts at zero.

Examples:

Element number	on-bits	off-bits
1	0010010101101	1010110101100
2	1110101001110	1001010101001
3	0110010100110	1000110001010
4	0110111001110	0010010100101
5	0010000101101	0000111100011



Taking the right-most bit of each mask to be bit 0, bits 2, 4, 9 and 10 of the on-masks are equivalent, whereas bits 4, 7 and 11 of the off-masks are equivalent. Hence allBitsEquiv() would return TRUE for bitNum=4 but not otherwise.

```
logical(bool) function allBitsEquiv(bitMasks, bitNum)
  type(BitMaskT), intent(in) :: bitMasks(:)
  integer(int32), intent(in) :: bitNum
end function allBitsEquiv
```

10 Subroutines for dumping test output to file or STDOUT

Module name: `dump`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

10.1 String content

Many ASCII codes are not associated with a printable character and thus it can be hard to determine all the characters in a string just by printing it to standard output. The present subroutine takes a string, chops it into individual characters, and prints the ASCII code of each character plus its associated printable character, if there is one.

```
subroutine dumpString(str)
  character(*), intent(in) :: str
end subroutine dumpString
```


10.2 Dumping images to FITS array

It is sometimes convenient to dump a 2-D array to a FITS dataset, without worrying about attributes or data type. The various overloadings of `dumpImageToFits` allow one to write an array of any numeric data type supported by the `dal`.

```
interface dumpImageToFits
  subroutine dumpImageToFitsSingle(image, setName)
    real(single), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
  end subroutine dumpImageToFitsSingle

  subroutine dumpImageToFitsDouble(image, setName)
    real(double), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
  end subroutine dumpImageToFitsDouble

  subroutine dumpImageToFitsInt8(image, setName)
    integer(int8), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
  end subroutine dumpImageToFitsInt8
```



```
subroutine dumpImageToFitsInt16(image, setName)
    integer(int16), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
end subroutine dumpImageToFitsInt16

subroutine dumpImageToFitsInt32(image, setName)
    integer(int32), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
end subroutine dumpImageToFitsInt32
```

The output data type for the last is actually 8-bit integer:

```
subroutine dumpImageToFitsBool_temp(image, setName)
    logical(bool), intent(in) :: image(:, :)
    character(*), intent(in) :: setName
end subroutine dumpImageToFitsBool_temp
end interface dumpImageToFits
```

11 Routines which deal with the geometry of ellipses

Module name: `ellipse`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

This module contains several routines for processing ellipses.

11.1 ‘Rotated’ and ‘phase’ formats

Dealing with ellipses is complicated by the fact that there are at least two convenient ways to parameterise an ellipse, which I will call the ‘rotated’ and ‘phase’ forms. In the ‘rotated’ form the ellipse is specified by two semiaxes R_x and R_y and a an angle of rotation α . In these terms the ellipse is specified most transparently by three equations:

$$\frac{x_0^2}{R_x^2} + \frac{y_0^2}{R_y^2} = 1 \quad (2)$$

$$x = x_0 \cos(\alpha) - y_0 \sin(\alpha)$$


$$y = y_0 \cos(\alpha) + x_0 \sin(\alpha).$$

The ellipse in ‘phase’ format is specified by two amplitudes A_x and A_y and a phase ϕ by two parametric equations in θ as follows:

$$x = A_x \cos(\theta) \quad (3)$$

$$y = A_y \cos(\theta + \phi). \quad (4)$$

If an ellipse is thought of as a squashed circle, θ is the angle around the original circle.



Rotations of coordinate system are easily accommodated in the ‘rotated’ format; changes of aspect ratio of the coordinate system are better accommodated in the ‘phase’ format.

Subroutines are given for translating between the two formats:

```
subroutine ellipsePhaseToAngle(xAmp, yAmp, phase&
, shortSemiAxis, longSemiAxis, rotatedAngle)

  real(single), intent(in) :: xAmp, yAmp, phase
  real(single), intent(out) :: longSemiAxis, shortSemiAxis, rotatedAngle
end subroutine ellipsePhaseToAngle

subroutine ellipseAngleToPhase(shortSemiAxis, longSemiAxis, rotatedAngle&
, xAmp, yAmp, phase)

  real(single), intent(in) :: longSemiAxis, shortSemiAxis, rotatedAngle
  real(single), intent(out) :: xAmp, yAmp, phase
end subroutine ellipseAngleToPhase
```

11.2 Is a given point inside a given ellipse?

Two routines are given for the two ellipse formats described above:

```
function pointInEllipseWithPhase(x, y, xAmp, yAmp, phase)
  real(single), intent(in) :: x, y, xAmp, yAmp, phase
  integer :: pointInEllipseWithPhase
end function pointInEllipseWithPhase

function pointInEllipseWithAngle(x, y, xSemiAxis, ySemiAxis, rotatedAngle)
  real(single), intent(in) :: x, y, xSemiAxis, ySemiAxis, rotatedAngle
  integer :: pointInEllipseWithAngle
end function pointInEllipseWithAngle
```

These functions return -1 if the point (x, y) lies fully within the ellipse; 0 if it is on the border; and 1 if it is fully outside the ellipse.

11.3 Generating a set of points along an ellipse locus

```
subroutine calcEllipseFromAngle(xSemi, ySemi, angleDeg, xVals, yVals)
  real(single), intent(in) :: xSemi, ySemi, angleDeg
  real(single), intent(out) :: xVals(:), yVals(size(xVals))
end subroutine calcEllipseFromAngle
```

Equation 2 can be decomposed into the following pair of parametric equations in θ :

$$x = R_x \cos(\theta)$$

$$y = R_y \sin(\theta).$$



θ here plays the same role as in equations 3 and 4. The subroutine returns points evenly distributed in θ .

The matching ‘phase’-style subroutine is

```
subroutine calcEllipseFromPhase(xAmp, yAmp, phase, xVals, yVals)
  real(single), intent(in) :: xAmp, yAmp, phase
  real(single), intent(out) :: xVals(:), yVals(size(xVals))
end subroutine calcEllipseFromPhase
```

Again the point coordinates returned in xVals and yVals are distributed evenly in θ .

11.4 EllipseT structure definition

A structure definition is provided:

```
type, public :: EllipseT
  real(single) :::&
    xAmp,&
    yAmp,&
    phase,& ! radians
    shortSemiAxis,&
    longSemiAxis,&
    rotatedAngle ! radians
  character(10) :: unit ! eg 'pixels', 'detxy', 'tanxy'
  logical(bool) :: isCircle
end type EllipseT
```

An overloaded subroutine is also provided to initialize a variable of this type:

```
interface initializeEllipseT
  subroutine initializeEllipseTScalar(ellipse)
    type(EllipseT), intent(out) :: ellipse
  end subroutine initializeEllipseTScalar

  subroutine initializeEllipseTVector(ellipse)
    type(EllipseT), intent(out) :: ellipse(:)
  end subroutine initializeEllipseTVector
end interface
```

For scalar or vector ellipse the values set are:

```
ellipse%xAmp      = 0.0
ellipse%yAmp      = 0.0
ellipse%phase     = 0.0
ellipse%shortSemiAxis = 0.0
ellipse%longSemiAxis = 0.0
ellipse%rotatedAngle = 0.0
ellipse%unit       = 'none'
ellipse%isCircle   = .false.
```



12 A module containing routines to perform calculations relating to exposure issues

Module name: `exposure`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

13 Some utilities and definitions for applications which make use of the FFTW library

Module name: `fftw_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

This module is meant to be used in conjunction with the Fast Fourier Transform package fftw which comes with the sas. The module contains a header in which some useful variables are declared, as well as the following routine:

```
function findNextHighest2357multiple(i) result(result)
    integer, intent(in) :: i
end function findNextHighest2357multiple
```

This function is designed to look for the smallest integer that satisfies the following conditions: (i) it is greater than or equal to the argument i; (ii) it is a product only of the numbers 2, 3, 5 and 7. The fftw transform works most efficiently on arrays which have dimensions which are products of small primes.

14 A module containing some useful type definitions

Module name: `geometric_types`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

The module defines the following types:

```
type, public :: Point2dT
    real(single) :: x, y
end type

type, public :: Point2dDbleT
    real(double) :: x, y
end type
```

15 Routines for constructing histograms

Module name: `histogram_utils`



Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

This module is still fairly undeveloped so I won't document it yet.

16 Routines to manipulate data of type IntervalT (see `caltypes`)

Module name: `intervals_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

The routines in this module offer ways to manipulate data structures of type IntervalT, which is defined in `caltypes`. These seem to be primarily of use for handling vectors of GTIs.

16.1 intervalsAreWellFormed

```
logical(bool) function intervalsAreWellFormed(intervals)
    type(IntervalT), intent(in) :: intervals(:)
end function intervalsAreWellFormed
```

Many of the other functions in the present section don't work unless the intervals are 'well-formed'. I define a well-formed vector of type IntervalT as obeying two conditions: (i) for each interval, the lower value must be \leq the upper; (ii) the upper value of interval i must be \geq the lower value of interval i+1. The function returns FALSE if either condition is disobeyed.

See section 9.5.1 for analogous conditions on structures of RangeT type.

16.2 isWithinInterval


```
logical(bool) function isWithinInterval(time, intervals, includeBoundary)
    real(double), intent(in)          :: time
    type(IntervalT), intent(in)       :: intervals(:)
    logical(bool), intent(in), optional :: includeBoundary
end function isWithinInterval
```

The argument 'time' is tested to see if it falls within any of the intervals. If optional argument 'includeBoundary' is included and set to TRUE, interval boundaries are considered: that is, for example, if `time=intervals(i)`

NOTE! This function requires the intervals to be well-formed (see section 16.1).

16.3 andIntervals

```
interface andIntervals
    subroutine andIntervalsBothScalar(intervalA, intervalB, andedIntervals)
```



```
    type(IntervalT), intent(in) :: intervalA, intervalB
    type(IntervalT), pointer     :: andedIntervals(:)
end subroutine andIntervalsBothScalar

subroutine andIntervalsOneVector(intervalA, intervalsB, andedIntervals)
    type(IntervalT), intent(in) :: intervalA, intervalsB(:)
    type(IntervalT), pointer     :: andedIntervals(:)
end subroutine andIntervalsOneVector

subroutine andIntervalsBothVector(intervalsA, intervalsB, andedIntervals)
    type(IntervalT), intent(in) :: intervalsA(:), intervalsB(:)
    type(IntervalT), pointer     :: andedIntervals(:)
end subroutine andIntervalsBothVector
end interface
```

In all cases the intervals are first converted to RangeT structures as follows:

```
range%lower%type = INCLUSIVE
range%upper%type = EXCLUSIVE
range%lower%value = interval%lower
range%upper%value = interval%upper
```

In this form, they can be ANDed together by use of the dss_aux call andRangesPair (see section 9.5.6)

NOTE! This function requires the intervals to be well-formed (see section 16.1).

16.4 orIntervals

```
interface orIntervals
    subroutine orIntervalsBothScalar(intervalA, intervalB, oredIntervals)
        type(IntervalT), intent(in) :: intervalA, intervalB
        type(IntervalT), pointer     :: oredIntervals(:)
    end subroutine orIntervalsBothScalar

    subroutine orIntervalsOneVector(intervalA, intervalsB, oredIntervals)
        type(IntervalT), intent(in) :: intervalA, intervalsB(:)
        type(IntervalT), pointer     :: oredIntervals(:)
    end subroutine orIntervalsOneVector

    subroutine orIntervalsBothVector(intervalsA, intervalsB, oredIntervals)
        type(IntervalT), intent(in) :: intervalsA(:), intervalsB(:)
        type(IntervalT), pointer     :: oredIntervals(:)
    end subroutine orIntervalsBothVector
end interface
```

In all cases the intervals are first converted to RangeT structures as follows:

```
range%lower%type = INCLUSIVE
```



```
range%upper%type = EXCLUSIVE
range%lower%value = interval%lower
range%upper%value = interval%upper
```

In this form, they can be ORed together by use of the dss_aux call orRangesPair (see section 9.5.7)

NOTE! This function requires the intervals to be well-formed (see section 16.1).

17 Least-squares fitting routines

Module name: `linear`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

Contains some routines to do with least-squares estimation and solution of linear equations.

17.1 stdDev

```
function stdDev(vector)
  real(single), intent(in) :: vector(:)
  real(single)             :: stdDev
end function stdDev
```

This find the average $\langle v \rangle$ of the input values v_i , then estimates the scatter or standard deviation σ of these values from

$$\sigma^2 = \frac{1}{N-1} \sum_i (v_i - \langle v \rangle)^2.$$

17.2 fitLine

```
subroutine fitLine(x, y, intercept, slope, variance, covar, status)
  real(single), intent(in)          :: x(:), y(size(x))
  real(single), intent(out)         :: intercept, slope
  real(single), intent(out), optional :: variance, covar(2, 2)
  integer,      intent(out), optional :: status
end subroutine fitLine
```

This fits a straight line to the set of points defined by x and y . The solution method is the standard one which assumes uncertainty in the y values only and solves the normal equations to arrive at a solution which minimizes the sum of the squares of the y -separation between the resulting line and each point.



17.3 fitPolynomial

```
subroutine fitPolynomial(x, y, coeffs, yVar, pinMask, chi2, errMatrix, status)
  real(single), intent(in)           :: x(:),&
                                         y(size(x))
  real(single), intent(inout)        :: coeffs(:)
  real(single), intent(in), optional :: yVar(size(x))
  logical(bool), intent(in), optional :: pinMask(size(coeffs))
  real(single), intent(out), optional :: chi2,&
                                         errMatrix(size(coeffs),&
                                         size(coeffs))
  integer,      intent(out), optional :: status
end subroutine fitPolynomial
```

This subroutine fits a polynomial to the set of points defined by *x* and *y*. The order of the polynomial is given by the size of the vector ‘coeffs’. As per usual, only the *y* values are assumed to have significant uncertainties. The subroutine solves normal equations to arrive at a solution which minimizes χ^2 between the data and the fitted polynomial.

Some or all of the coefficients can be ‘pinned’ or not fitted. These values should be supplied in the vector ‘coeff’ (note that this is of intent ‘inout’ as required). The appropriate members of ‘pinMask’ should be set to TRUE; all other members of ‘pinMask’ should of course be FALSE. For example, suppose it was desired to fit to the data a function of the form $y(x) = a + cx^2$. This is equivalent to fitting a full quadratic function to the data, but with the linear coefficient pinned at 0. To achieve this result, ‘coeff’ and ‘pinMask’ should be of size 3, with the following values set:

```
coeff(2) = 0.0
pinMask = /(.false. .true. .false.)/
```

The general form of the normal equations in the event of pinning is perhaps best illustrated by using the above example. In this case the equations are

Note that the matrix of uncertainties in the fitted coefficients as well as the χ^2 value at the optimum are also returned.

17.4 solveLinearTriDiag

17.5 solveLinearEquations

17.6 invertPosDefMatrix



18 Miscellaneous mathematical utilities

Module name: `math_utils`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

19 Function minimization routines

Module name: `minimizations`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

20 Helper subroutines for handling ODF (OAL)

Module name: `oal_aux`

Author: Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

In any of the following task, the environmental variable `SAS_ODF` should be properly set before the call.

20.1 printODFProposal

Dumps the proposal information derived from the ODF.

```
interface printODFProposal
    subroutine printODFProposal(proposalInfo, printHeader)
        type(ProposalInfoType), intent(in) :: proposalInfo
        logical, intent(in), optional      :: printHeader
    end subroutine printODFProposal
end interface
```

The optional parameter `printHeader` specifies whether the header is also printed to STDOUT (T) or not (F). The default is True.

Note that `proposalInfo` is obtained via

```
call OAL_proposalInfo(proposalInfo)
```

21 List Parsing

Module name: `parse_list_mod`

Author: Dean Hinshaw (NASA/GFSC, dah@milkway.gsfc.nasa.gov)



This subroutine parses a string containing a delimited list into an array of strings, one element for each member of the list. The calling sequence is:

```
SUBROUTINE parse_list(in_str, out_array, in_delim)

CHARACTER(LEN=*), DIMENSION(:), POINTER :: out_array
CHARACTER(LEN=*),                :: in_str
CHARACTER(LEN=1), OPTIONAL, INTENT(IN) :: in_delim
```

where `in_str` is the string to be parsed, `out_array` is returned array of strings, and `in_delim` is the delimiter separating the list items. `in_delim` is an optional parameter, and if not given defaults to a space. Note that in any case list items may not contain spaces. The user also must take care that the pointer passed as `out_array` has sufficient length to hold the parsed strings.

Additional, if `in_str` begins with an “@”, then the string is taken as a filename the list items, one item for each line of the file.

22 A tool to regrid data from one 2D pixel grid to another

Module name: `polygon`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

23 Contains an analytic approximation to the off-axis PSF, and routines to sample it.

Module name: `psf_ims`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

24 Routines to return random numbers in various distributions

Module name: `random_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

25 Array Reallocation

Module name: `reallocate`

Author: Dean Hinshaw (NASA/GFSC, dah@milkway.gsfc.nasa.gov)

This subroutine can be used to reallocate memory space for a pointer to an array, retaining any data already stored in the array. The calling sequence is:



```
SUBROUTINE realloc_real32(p, n)
```

```
    INTEGER, INTENT(in) :: n
```

where `p` can have any of the possible specifications:

```
REAL(KIND=single),   POINTER, DIMENSION(:) :: p
REAL(KIND=double),  POINTER, DIMENSION(:) :: p
INTEGER(KIND=int8),  POINTER, DIMENSION(:) :: p
INTEGER(KIND=int16), POINTER, DIMENSION(:) :: p
INTEGER(KIND=int32), POINTER, DIMENSION(:) :: p
LOGICAL(KIND=bool), POINTER, DIMENSION(:) :: p
CHARACTER(LEN=*),   POINTER, DIMENSION(:) :: p
```

and `n` is the size of the reallocated array. The lower bound value of the old array is retained.

If `n` is greater than the original array size, then the all data from the old array is retained, and the array values greater than the original array size are undefined. If `n` is less than the original array size, then the first `n` data elements from the old array are retained.

26 Utilities to rebin 1D or 2D data between parallel pixel grids

Module name: `rebinnings`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

27 Short cuts to saving (or overwriting) output images

Module name: `save_image`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

28 Quick Sorting

Module name: `sort_mod`

Author: Clive Page (University of Leicester, cgp@star.le.ac.uk)

This module contains subroutines to sort a data array into ascending order using Hoare's quick-sort algorithm. There is a generic interface which supports data types `INTEGER`, `REAL`, `DOUBLE PRECISION`, and `CHARACTER` (any length).

The simplest call is:

```
CALL quick_sort(array)
```



The array argument has `INTENT(INOUT)` and returns the data sorted into ascending order.

In some cases it is desirable to know the original order of the data points, for example to sort another array in the same way. In this case an optional second argument may be given; it returns an integer array of the same size containing numbers in the range 1 to `size(array)` which tell you the original position of each element returned sorted. For example if you do:

```
unsorted_array = array
call quick_sort(array, index)
```

then `unsorted_array(index(i)) = array(i)` for all i in $[lbound(array), ubound(array)]$. Note that array is always returned sorted, whether index is supplied or not. This can be something to be careful of. Suppose you have a data structure array which you want to sort in order of one of its constituents, for example a structure that stores gtis:

```
type :: gtiType
  real(kind(0d0)) :: time
  logical          :: isStart
end type gtiType
type(gtiType) :: gtiArray(100)

! Fill gtiArray
```

In this case to sort the logicals as well you will need to do something like the following:

```
type(gtiType) :: temp_gtiArray(size(gtiArray))

temp_gtiArray%time = gtiArray%time
call quick_sort(temp_gtiArray%time, index)
do i = 1, size(gtiArray)
  temp_gtiArray(i)%isStart = gtiArray(index(i))%isStart
! NOT temp_gtiArray(i) = gtiArray(index(i))!! The times are already sorted.
end do
gtiArray = temp_gtiArray
```

Note that the quick-sort algorithm is on average about twice as fast as heap-sort but becomes much slower for special cases. This quick-sort algorithm was designed to cope with nearly-sorted data as well as random data without any significant degradation in speed. Note that it is *not* a stable sort, i.e. equal values will not necessarily remain in the same relative order.

29 A routine which returns circles or ellipses to mark source locations

Module name: `source_cutouts`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)



30 1D and 2D cubic-spline routines

Module name: `splines`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

31 Miscellaneous utilities

Module name: `ssc_misc`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk) (except for `getFreeIoUnit`)

31.1 Find a Free I/O Unit

Author: Clive Page (University of Leicester, cgp@star.le.ac.uk)

This subroutine returns a number of a free I/O unit, i.e. one that is not currently allocated to and file. The calling sequence is:

```
SUBROUTINE getFreeIoUnit(nunit)
  INTEGER, INTENT(out) :: nunit    ! unit number free for use
```

32 Some functions for testing/debugging

Module name: `test_utils`

Author: Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

The subroutines/functions in this module provide functions that are useful in testing (and possibly debugging).

32.1 `isNearlyEqual()`: Comparing numbers with a given precision

This function returns `.true.` if the given pair of values agree with each other in the given precision (order), or `.false.` otherwise.

```
LOGICAL(bool) FUNCTION isNearlyEqual(cmp, compared, precision)
  REAL, intent(in) :: cmp, compared    ! or INTEGER
  INTEGER, intent(in) :: precision
END FUNCTION isNearlyEqual
```

For the pair of the first two arguments, any combination of `int8`, `int16`, `int32`, `single` and `double` is allowed.



32.1.1 Examples

```
isNearlyEqual(1110, 1112, 3) returns .true.  
isNearlyEqual(1.2, 1.0, 3) returns .false.  
isNearlyEqual(1.234, 1.231, 3) returns .true.  
isNearlyEqual(1.2349, 1.2351, 3) returns .true.
```

33 Routines to perform hyperbolic distortion of values in the interval [0:1]

Module name: `warp_utils`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

34 Utilities to assist in the reading and manipulation of WCS keywords

Module name: `wcs_aux`

Author: Ian Stewart (University of Leicester, ims@star.le.ac.uk)

35 Utilities to assist development in Perl

Module name: `SSCLib`

Author: Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

See the header of the library code for detail. You may want to read it by, for example, `cd /YOUR/DIR; pod2man SSCLib.pm | tbl | neqn | nroff -h -man | less`

36 General coordinates class in Perl

Module name: `Coords`

Author: Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

See the header of the library code for detail. You may want to read it by, for example, `cd /YOUR/DIR; pod2man Coords.pm | tbl | neqn | nroff -h -man | less`



37 Celestial coordinates utilities in Perl

Module name: `CelCoords`

Author: Masaaki Sakano (University of Leicester, mas@star.le.ac.uk)

See the header of the library code for detail. You may want to read it by, for example, `cd /YOUR/DIR; pod2man CelCoords.pm | tbl | neqn | nroff -h -man | less`

References